


Honeywell Sensing and Control

Home> Products > MICRO SWITCH™ Toggle Switches > TL > Product Page

■ Order Product and **Get Support**

- U.S. Authorized Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback

101TL2834-3



position, IWTS (16-20 Gage) terminal, **Standard Lever**

TL Series Toggle Switch, 1 pole, 2

Keyword Search Search for product and support information. All Sensing and Contro

Product Search Part number search:

Use (*) to expand search

Specification Search

Features

Environmentproof sealing 1,2, and 4 pole circuitry Standard and pull-to-unlock levers 2 and 3 position, maintained and momentary toggle action Temperature range:-85? F to +160? F Completely sealed switching chamber Step-design case provides added space between terminals to help prevent shorting UL recognized, CSA certified CE approved

Actual product appearance may vary.

Potential Applications

Industrial machinery and equipment Military and commercial aviation Construction equipment Test instruments Agricultural machinery Process control Medical instrumentation

Description

MICRO SWITCH™TL Series toggle switches have high strength, temperature resistant, non-tracking case material and silver cadmium oxide contacts. Pulto-Unlock toggle levers prevent accidental operation; the lever must be pulled approx. 2,3 mm (0.09 inches) to change positions.

Gold Plated Contacts

30211908 Toggle switches

Standard

Global

TL

30211908

Supporting Documentation

■ Accessory: Lever Sleeve Engineering

Drawing

Product Type

Load)

Circuitry

Mounting

Termination Lever Type

Comment

Availability

UNSPSC Code

Series Name

UNSPSC Commodity

Ampere/Voltage Range (Resistive

Accessory: Seals

Accessory: Nuts

	Product Specifications
Circuitry/Operating action	Keyway Position 1 2 3

Keyway Keyway Position	
1 2 3 1 2 3 ON ON	
MICRO SWITCH™ Toggle Switch	
0.01 A to 0.1 A at 0.5 Vdc to 28 Vdc,0.01 A to 0.1 A at 0.5 Vac to 115 Vac	
SPDT	
2 position	
Bushing 15/32 in	
IWTS (16 - 20 Gage)	

Opposite