


Honeywell Sensing and Control

Order Product and Get Support

- U.S. Authorized Distributors
- Global Sales & Service
- Global Sales & ServiceN. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback

Home> Products > MICRO SWITCH™ Toggle Switches > TL > Product Page

102TL1-1E



TL Series Toggle Switch, 2 pole, 3 position, IWTS (14-16 Gage) terminal, Locking Lever, Military Part Number MS27782-21E

Keyword Search

Search for product and support information.

All Sensing and Contro

Product Search

Part number search:

Use (*) to expand search

Specification Search

Features

Qualified to MILS-3950
Environmentproof sealing
1,2, and 4 pole circuitry
Standard and pull-to-unlock levers
2 and 3 position, maintained and
momentary toggle action
Temperature range:-85? F to +160? F
Completely sealed switching chamber
Step-design case provides added
space between terminals to help
prevent shorting
UL recognized, CSA certified
CE approved

Actual product appearance may vary.

Potential Applications

Industrial machinery and equipment
Military and commercial aviation
Construction equipment
Test instruments
Agricultural machinery
Process control
Medical instrumentation

Description

MICRO SWITCH™TL Series toggle switches have high strength, temperature resistant, non-tracking case material and silver cadmium oxide contacts. Pułto-Unlock toggle levers prevent accidental operation; the lever must be pulled approx. 2,3 mm (0.09 inches) to change positions.

Supporting Documentation

Accessory: Seals



Engineering Drawing

Product Specifications			
Circuitry/Operating action		Center Position 1 2 3 6 5 4	Opposite Keyway Position 1 2 3 6 5 4 ON
Product Type	MICRO SWITCH™ To	OFF oggle Switch	ON
Lever Lock	Locked in center position		
Ampere/Voltage Range (Resistive Load)	0.5 A to 15 A at 0.5 Vac to 277 Vac,0.5 A to 20 A at 0.5 Vdc to 28 Vdc,0.75 A at 115 Vdc,0.5 A at 250 Vdc		
Circuitry	DPDT		
Action	3 position		
Mounting	Bushing 15/32 in		
Termination	IWTS (14 - 16 Gage)		
Military Part Number	MS27782 -21E		
Lever Type	Locking		
UL/CSA Rating Code	L191: 15 A - 125, 250, 277 Vac; 1/2 Hp - 125 Vac; 1 Hp - 250, 277 Vac; 5 A - 120 Vac "L"		
Comment	Silver cadmium oxide	contacts	
Availability	Global		
UNSPSC Code	30211908		
UNSPSC Commodity	30211908 Toggle switches		
Series Name	TL		