


Honeywell Sensing and Control

Home> Products > Power-duty Rocker Switches > TP > Product Page

Order Product and **Get Support**

- U.S. Authorized **Distributors**
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback

104TP82-3



TP Series Rocker Switch, 4 pole, 2 position, IWTS (16-20 Gage) terminal, **Above Panel Mounting**

Actual product appearance may vary.

Features

Gold or silver contacts Choice of sealed bushing Standard or pull to unlock toggle lever Short behind-panel depth Solder or quick connect termination 2,4, 6, or 8 SPDT precision basic switches

2 or 3 position, momentary or maintained action

Potential Applications

Industrial machinery and equipment Military and commercial aviation Construction equipment Test instruments Agricultural machinery Process control Medical instrumentation

Description

Compact multipole 2, 4, 6,or 8 SPDT design. MICRO SWITCH™ precision basic switches conserve space and weight. Pull -to-Unlock Toggle Levers prevent accidental operation: the lever must be pulled approximately 2,3 mm [0.09 inches] to change the positions. Many locking configurations are available. Lever to bushing seals. Hermetic basic switches are available. AT qualified versions meet MILS-8805/98. Various levers and styles are available.

Product Specifications

Supporting Documentation

Engineering Drawing

Circuitry/Operating action	Opposite Keyway Keyway Position Position
	3 2 1 3 2 1
	9 8 7 9 8 7 12 11 10 12 11 10 ON ON
Product Type	MICRO SWITCH™ Rocker
Ampere/Voltage Range (Resistive Load)	0.5 A to 15 A at 0.5 Vac to 277 Vac,0.5 A to 20 A at 0.5 Vdc to 28 Vdc,0.5 A at 250 Vdc,0.75 A at 115 Vdc
Circuitry	4PDT
Action	2 position
Mounting	Above Panel
Termination	IWTS (16 - 20 Gage)
Button Type	No button
UL/CSA Rating Code	L191: 15 A - 125, 250, 277 Vac; 1/2 Hp - 125 Vac; 1 Hp - 250, 277 Vac; 5 A - 120 Vac "L"
Comment	Silver cadmium oxide contacts
Availability	Global
UNSPSC Code	302119
UNSPSC Commodity	302119 Switches and controls and relays
Series Name	TP

My Links

Login to iCOM Login as Rep/AD **Login as Guest Login to Digital** University

Keyword Search

Search for product and support information.

All Sensing and Contro

Product Search

Part number search:

Use (*) to expand search

Specification Search