




Home> Products > MICRO SWITCH™ Toggle Switches> TW> Product Page

12TW401-21



Actual product appearance may vary.

TW Series Toggle Switch, 2 pole, 3 position, Solder terminal, Tab Lever

Features

- Save space and weight
- SPDT and DPDT circuitry
- Temperature range: -85° F to +160° F (-65° C to +71° C)
- Sealed bushing versions
- Choice of 1/8 in. or 15/32 in. bushing
- Color tab available on 15/32 in. bushing
- UL recognized

Potential Applications

- Industrial machinery and equipment
- Military and commercial aviation
- Construction equipment
- Test instruments
- Agricultural machinery
- Process control
- Medical instrumentation

Description

MICRO SWITCH™ miniature toggle switches in two bushing sizes. Molded in terminals are plated for soldering. Momentary and maintained circuitry closures available. Special on-on-on circuitries are also available. Pull-to-unlock levers prevent accidental operation.

Supporting Documentation

- Accessory: Lever Sleeve
- Accessory: Seals
- Accessory: Nuts
- Engineering Drawing

Product Specifications		
Circuitry/Operating action	Center Maintained Position Opposite Maintained Keyway Position	
Product Type	MICRO SWITCH™ Toggle Switch	
Ampere/Voltage Range (Resistive Load)	0.1 A to 5.0 A at 0.5 Vac to 115 Vac, 0.1 A to 5.0 A at 0.5 Vdc to 28 Vdc	
Circuitry	DPST	
Action	3 position	
Mounting	Bushing 15/32 in	
Termination	Solder	
Lever Type	Tab	
UL/CSA Rating Code	L117: 5 A at 125 Vac	
Comment	Fine silver contacts	
Availability	Global	
UNSPSC Code	30211908	
UNSPSC Commodity	30211908 Toggle switches	
Series Name	TW	

My Links

- Login to iCOM
- Login as Rep/AD
- Login as Guest
- Login to Digital University

Keyword Search

Search for product and support information.

All Sensing and Control

Product Search

Part number search:

Use (*) to expand search

Specification Search