

# **Honeywell Sensing and Control**

Home> Products > MICRO SWITCH™ Toggle Switches > TW > Product Page

# Order Product and **Get Support**

- U.S. Authorized Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback

# 12TW75-3



TW Series Toggle Switch, 2 pole, 2 position, Solder T2 Type terminal, **Standard Lever** 

Actual product appearance may vary.

#### **Features**

Save space and weight SPDT and DPDT circuitry Temperature range:-85? F to +160? F (- Construction equipment 65? C to +71? C) Sealed bushing versions Choice of? in. or 15/32 in. bushing Color tab available on 15/32 in. bushing UL recognized

#### **Potential Applications**

Industrial machinery and equipment Military and commercial aviation Test instruments Agricultural machinery Process control Medical instrumentation

## **Description**

MICRO SWITCH™ miniature toggle switches in two bushing sizes. Moldedin terminals are plated for soldering. Momentary and maintained circuitry closures available. Special on-on-on circuitries are also available. Pullto-unlock levers prevent accidental operation.

# **Supporting Documentation**

Accessory: Lever Sleeve

Accessory: Seals

Accessory: Nuts



Product Specifications	
Circuitry/Operating action	Copposite Keyway Position Position  1 2 3 1 2 3 6 5 4 6 5 4 ON ON
Product Type	MICRO SWITCH™ Toggle Switch
Ampere/Voltage Range (Resistive Load)	0.1 A to 5.0 A at 0.5 Vdc to 28 Vdc,0.1 A to 5.0 A at 0.5 Vac to 115 Vac
Circuitry	DPDT
Action	2 position
Mounting	Bushing 15/32 in
Termination	Solder T2 type
Lever Type	Standard
UL/CSA Rating Code	L117: 5 A at 125 Vac
Comment	Fine silver contacts
Availability	Global
UNSPSC Code	30211908
UNSPSC Commodity	30211908 Toggle switches
Series Name	TW

### My Links

Login to iCOM Login as Rep/AD Login as Guest **Login to Digital** University

# **Keyword Search**

Search for product and support information.

All Sensing and Contro

# Product Search

Part number search:

Use (\*) to expand search

**Specification Search**