

Honeywell Sensing and Control

Home> Products > MICRO SWITCH™ Toggle Switches > TW > Product Page

Order Product and **Get Support**

- U.S. Authorized Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback

12TW873-1



TW Series Toggle Switch, 2 pole, 3 position, Solder terminal, Standard Lever

Actual product appearance may vary.

Features

Save space and weight SPDT and DPDT circuitry Temperature range:-85? F to +160? F (- Construction equipment 65? C to +71? C) Sealed bushing versions Choice of? in. or 15/32 in. bushing Color tab available on 15/32 in. bushing UL recognized

Potential Applications

Industrial machinery and equipment Military and commercial aviation Test instruments Agricultural machinery Process control Medical instrumentation

Description

MICRO SWITCH™ miniature toggle switches in two bushing sizes. Moldedin terminals are plated for soldering. Momentary and maintained circuitry closures available. Special on-on-on circuitries are also available. Pullto-unlock levers prevent accidental operation.

Supporting Documentation

Accessory: Lever

Accessory: Seals

Accessory: Nuts



Product Specifications			
Circuitry/Operating action	Keyway Position 1 2 3 6 5 4 ON	Center Position 1 2 3 6 5 4 OFF	Opposite Keyway Position 1 2 3 6 5 4 ON
Product Type	MICRO SWITCH™ Toggle Switch		
Ampere/Voltage Range (Resistive Load)	0.01 A to 0.1 A at 0.5 Vdc to 28 Vdc,0.01 A to 0.1 A at 0.5 Vac to 115 Vac		
Circuitry	DPDT		
Action	3 position		
Mounting	Bushing 15/32 in		
Termination	Solder		
Lever Type	Standard		
Comment	Gold Plated Contacts		
Availability	Global		
UNSPSC Code	30211908		
UNSPSC Commodity	30211908 Toggle switches		
Series Name	TW		

Site Map

My Links

Login to iCOM Login as Rep/AD Login as Guest **Login to Digital** University

Keyword Search

Search for product and support information.

All Sensing and Contro

Product Search

Part number search:

Use (*) to expand search

Specification Search