


# **Honeywell Sensing and Control**

Home> Products > MICRO SWITCH™ Toggle Switches > TL > Product Page


## Order Product and **Get Support**

- U.S. Authorized Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback

## 1TL887-1N



TL Series Toggle Switch, 1 pole, 3 position, Screw terminal, Locking



Part number search:

Use (\*) to expand search

**Specification Search** 

#### **Features**

Environmentproof sealing 1,2, and 4 pole circuitry Standard and pull-to-unlock levers 2 and 3 position, maintained and momentary toggle action Temperature range:-85? F to +160? F Completely sealed switching chamber Step-design case provides added space between terminals to help prevent shorting UL recognized, CSA certified

Actual product appearance may vary.

## **Potential Applications**

Industrial machinery and equipment Military and commercial aviation Construction equipment Test instruments Agricultural machinery Process control Medical instrumentation

#### **Description**

CE approved

MICRO SWITCH™TL Series toggle switches have high strength, temperature resistant, non-tracking case material and silver cadmium oxide contacts. Pulto-Unlock toggle levers prevent accidental operation; the lever must be pulled approx. 2,3 mm (0.09 inches) to change positions.

# **Supporting Documentation**

Accessory: Seals

Accessory: Nuts

Engineering **Drawing** 

Product Specifications			
Circuitry/Operating action	Keyway Position	Center Position	Opposite Keyway Position
Product Type	ON MICRO SWITCHT	OFF  M Toggle Switch	ON
Lever Lock	MICRO SWITCH™ Toggle Switch		
LEVEL LOCK	Locked out o extreme position (Opposite keywo	on	
Ampere/Voltage Range (Resistive Load)	0.5 A at 250 Vdc,0.75 A at 115 Vdc,0.5 A to 15 A at 0.5 Vac to 277 Vac,0.5 A to 20 A at 0.5 Vdc to 28 Vdc		
Circuitry	SPDT		
Action	3 position		
Mounting	Bushing 15/32 in		
Termination	Screw		
Lever Type	Locking		
UL/CSA Rating Code	L191: 15 A - 125, 250, 277 Vac; 1/2 Hp - 125 Vac; 1 Hp - 250, 277 Vac; 5 A - 120 Vac "L"		
Comment	Gold Plated Contacts		
Availability	Global		
UNSPSC Code	30211908		
UNSPSC Commodity	30211908 Toggle switches		
Series Name	TL		