


Honeywell Sensing and Control

Home> Products > MICRO SWITCH™ Toggle Switches > TL > Product Page

Order Product and Get Support

- U.S. Authorized Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback

1TL887-7E



TL Series Toggle Switch, 1 pole, 3 position, Screw terminal, Locking Lever



Part number search:

Use (*) to expand search

Specification Search

Features

Environmentproof sealing
1,2, and 4 pole circuitry
Standard and pull-to-unlock levers
2 and 3 position, maintained and
momentary toggle action
Temperature range:-85? F to +160? F
Completely sealed switching chamber
Step-design case provides added
space between terminals to help
prevent shorting
UL recognized, CSA certified
CE approved

Potential Applications

Industrial machinery and equipment Military and commercial aviation Construction equipment Test instruments Agricultural machinery Process control Medical instrumentation

Description

MICRO SWITCH™TL Series toggle switches have high strength, temperature resistant, non-tracking case material and silver cadmium oxide contacts. Pułto-Unlock toggle levers prevent accidental operation; the lever must be pulled approx. 2,3 mm (0.09 inches) to change positions.

Supporting Documentation

Accessory: Seals

Accessory: Nuts

Engineering Drawing

Product Specifications		
Circuitry/Operating action	Keyway Momentary Center Position Position 1 2 3 1 2 3 ON OFF	Opposite Keyway Momentary Position 1 2 3 ON
Product Type	MICRO SWITCH™ Toggle Switch	
Lever Lock	Locked in center position	
Ampere/Voltage Range (Resistive Load)	0.5 A to 15 A at 0.5 Vdc to 28 Vdc,0.5 A to 10 A at 0.5 Vac to 7 Vac,0.75 A at 115 Vdc,0.5 A at 250 Vdc	
Circuitry	SPDT	
Action	3 position	
Mounting	Bushing 15/32 in	
Termination	Screw	
Lever Type	Locking	
UL/CSA Rating Code	L192: 10 A -125, 250, 277 Vac; 1/4 Hp Hp - 250, 277 Vac; 3 A -125 Vac "L"	- 125 Vac; 1/2
Comment	Gold Plated Contacts	
Availability	Global	
UNSPSC Code	30211908	
UNSPSC Commodity	30211908 Toggle switches	
Series Name	TL	