


Honeywell Sensing and Control

Home> Products > Power-duty Rocker Switches > TP> Product Page

Order Product and **Get Support**

- U.S. Authorized Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback

1TP65-5



TP Series Rocker Switch, 1 pole, 3 position, Screw terminal, Above Panel Mounting

Actual product appearance may vary.

Features

Environmentally sealed Two and three-position pushbutton action Various button colors 1, 2, and 4-pole circuitry Flush panel and above panel mountings Temperature range: -54 ? C to +71? C [-65 ? F to +160 ? F]

UL recognized, CSA certified CE approved

Potential Applications

Military and commercial aviation Marine applications Construction equipment Test instruments Agricultural machinery Process control Medical instrumentation

Industrial machinery and equipment

My Links

Login to iCOM Login as Rep/AD

Login as Guest

Login to Digital University

Search for product and

All Sensing and Contro

support information.

Keyword Search

Product Search

Part number search:

Use (*) to expand search

Specification Search

Description

MICRO SWITCH™ TP Rocker switches may be mounted flush with panel for a lowbutton profile or above panel for a distinct button appearance. Buttons measure 22,1 mm x 37,1 mm [.87 in x 1.46 in]. They are removable and interchangeable, and come in transparent plastic, translucent plastic, and six colors of opaque plastic. Switches without buttons are also available, as well as separate buttons.

Supporting Documentation





Product Specifications	
Circuitry/Operating action	Keyway Momentary Center Position
Product Type	MICRO SWITCH™ Rocker
Ampere/Voltage Range (Resistive Load)	0.5 A to 15 A at 0.5 Vdc to 28 Vdc,0.5 A to 10 A at 0.5 Vac to 7 Vac,0.75 A at 115 Vdc,0.5 A at 250 Vdc
Circuitry	SPDT
Action	3 position
Mounting	Above Panel
Termination	Screw
Button Type	Transparent
UL/CSA Rating Code	L192: 10 A - 125, 250, 277 Vac; 1/4 Hp - 125 Vac; 1/2 Hp - 250, 277 Vac; 3 A - 125 Vac "L"
Comment	No mounting tabs
Availability	Global
UNSPSC Code	302119
UNSPSC Commodity	302119 Switches and controls and relays
Series Name	TP