


Honeywell Sensing and Control

Home> Products > Power-duty Rocker Switches > TP > Product Page

Order Product and **Get Support**

- U.S. Authorized Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback

1TP7-1



TP Series Rocker Switch, 1 pole, 3 position, Screw terminal, Above Panel Mounting

Features

Environmentally sealed Two and three-position pushbutton action Various button colors 1, 2, and 4-pole circuitry Flush panel and above panel mountings Temperature range: -54 ? C to +71? C [-65 ? F to +160 ? F] UL recognized, CSA certified

Actual product appearance may vary.

Industrial machinery and equipment Military and commercial aviation Marine applications Construction equipment Test instruments Agricultural machinery Process control Medical instrumentation

Potential Applications

Product Search Part number search: Use (*) to expand search **Specification Search**

My Links

Login to iCOM Login as Rep/AD

Login as Guest

Login to Digital University

Search for product and

All Sensing and Contro

support information.

Keyword Search

Description

CE approved

MICRO SWITCH™ TP Rocker switches may be mounted flush with panel for a lowbutton profile or above panel for a distinct button appearance. Buttons measure 22,1 mm x 37,1 mm [.87 in x 1.46 in]. They are removable and interchangeable, and come in transparent plastic, translucent plastic, and six colors of opaque plastic. Switches without buttons are also available, as well as separate buttons.

Supporting Documentation



Engineering **Drawing**

Product Specifications				
Circuitry/Operating action		enter osition	Opposite Keyway Position	
	1 2 3 1 ON	2 3 OFF	1 2 3 ON	
Product Type	MICRO SWITCH™ Rocker			
Ampere/Voltage Range (Resistive Load)	0.5 A at 250 Vdc,0.75 A at 115 Vdc,0.5 A to 15 A at 0.5 Vac to 277 Vac,0.5 A to 20 A at 0.5 Vdc to 28 Vdc			
Circuitry	SPDT			
Action	3 position			
Mounting	Above Panel			
Termination	Screw			
Button Type	No button			
UL/CSA Rating Code	L191: 15 A - 125, 250, 277 Vac; 1/2 Hp - 125 Vac; 1 Hp - 250, 277 Vac; 5 A - 120 Vac "L"			
Comment	Silver cadmium oxide contacts			
Availability	Global			
UNSPSC Code	302119			
UNSPSC Commodity	302119 Switches and controls and relays			
Series Name	TP	TP		