


## **Honeywell Sensing and Control**

Home> Products > Power-duty Rocker Switches > TP> Product Page

#### Order Product and **Get Support**

- U.S. Authorized Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback

#### 1TP7-2-BK



TP Series Rocker Switch, 1 pole, 2 position, Screw terminal, Above Panel Mounting

Actual product appearance may vary.

### **Features**

Environmentally sealed Two and three-position pushbutton action Various button colors 1, 2, and 4-pole circuitry Flush panel and above panel mountings Temperature range: -54 ? C to +71? C [-65 ? F to +160 ? F] UL recognized, CSA certified

#### **Potential Applications**

Industrial machinery and equipment Military and commercial aviation Marine applications Construction equipment Test instruments Agricultural machinery Process control Medical instrumentation

# **Product Search** Part number search: Use (\*) to expand search **Specification Search**

My Links

Login to iCOM Login as Rep/AD

Login as Guest

**Login to Digital** University

Search for product and

All Sensing and Contro

support information.

Keyword Search

#### Description

CE approved

MICRO SWITCH™ TP Rocker switches may be mounted flush with panel for a lowbutton profile or above panel for a distinct button appearance. Buttons measure 22,1 mm x 37,1 mm [.87 in x 1.46 in]. They are removable and interchangeable, and come in transparent plastic, translucent plastic, and six colors of opaque plastic. Switches without buttons are also available, as well as separate buttons.

### **Supporting Documentation**

Accessory: Rocker **Operator** 

Product Specifications	
Circuitry/Operating action	Opposite Keyway Position Position  2 3 2 3 OFF ON
Product Type	MICRO SWITCH™ Rocker
Ampere/Voltage Range (Resistive Load)	0.5 A at 250 Vdc,0.75 A at 115 Vdc,0.5 A to 15 A at 0.5 Vac to 277 Vac,0.5 A to 20 A at 0.5 Vdc to 28 Vdc
Circuitry	SPST
Action	2 position
Mounting	Above Panel
Termination	Screw
Button Type	No button
UL/CSA Rating Code	L191: 15 A -125, 250, 277 Vac; 1/2 Hp -125 Vac; 1 Hp -250, 277 Vac; 5 A -120 Vac "L"
Comment	Silver cadmium oxide contacts
Availability	Global
UNSPSC Code	302119
UNSPSC Commodity	302119 Switches and controls and relays
Series Name	TP