




Home > Products > Power-duty Rocker Switches > TP > Product Page

Order Product and Get Support

- U.S. Authorized Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback

1TP910-3



Actual product appearance may vary.

TP Series Rocker Switch, 1 pole, 2 position, Quick Connect terminal, Flush Panel Mounting

Features

Environmentally sealed
 Two and three-position pushbutton action
 Various button colors
 1, 2, and 4-pole circuitry
 Flush panel and above panel mountings
 Temperature range: -54 °C to +71 °C [-65 °F to +160 °F]
 UL recognized, CSA certified
 CE approved

Potential Applications

Industrial machinery and equipment
 Military and commercial aviation
 Marine applications
 Construction equipment
 Test instruments
 Agricultural machinery
 Process control
 Medical instrumentation

Description

MICRO SWITCH™ TP Rocker switches may be mounted flush with panel for a low-button profile or above panel for a distinct button appearance. Buttons measure 22,1 mm x 37,1 mm [.87 in x 1.46 in]. They are removable and interchangeable, and come in transparent plastic, translucent plastic, and six colors of opaque plastic. Switches without buttons are also available, as well as separate buttons.

Supporting Documentation

- [Accessory: Rocker Operator](#)
- [Engineering Drawing](#)

Product Specifications	
Circuitry/Operating action	<div style="display: flex; justify-content: space-around;"> <div style="text-align: center;"> <p>Keyway Position</p> <p>1 2 3 ON</p> </div> <div style="text-align: center;"> <p>Opposite Keyway Position</p> <p>1 2 3 ON</p> </div> </div>
Product Type	MICRO SWITCH™ Rocker
Ampere/Voltage Range (Resistive Load)	0.5 A at 250 Vdc, 0.75 A at 115 Vdc, 0.5 A to 15 A at 0.5 Vac to 277 Vac, 0.5 A to 20 A at 0.5 Vdc to 28 Vdc
Circuitry	SPDT
Action	2 position
Mounting	Flush Panel
Termination	Quick Connect
Button Type	Transparent
UL/CSA Rating Code	L191: 15 A - 125, 250, 277 Vac; 1/2 Hp - 125 Vac; 1 Hp - 250, 277 Vac; 5 A - 120 Vac "L"
Comment	Silver cadmium oxide contacts
Availability	Global
UNSPSC Code	302119
UNSPSC Commodity	302119 Switches and controls and relays
Series Name	TP

My Links

[Login to iCOM](#)
[Login as Rep/AD](#)
[Login as Guest](#)
[Login to Digital University](#)

Keyword Search

Search for product and support information.

All Sensing and Control

Product Search

Part number search:

Use (*) to expand search

[Specification Search](#)