


Honeywell Sensing and Control

 $Home \gt Products \gt MICRO \ SWITCH^{\intercal M} \ Toggle \ Switches \gt TL \gt Product \ Page$

Order Product and Get Support

- U.S. Authorized Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback

2TL11-10N



TL Series Toggle Switch, 2 pole, 3 position, Screw terminal, Locking Lever

Search for product and support information.

All Sensing and Contro

Product Search

Part number search:

Use (*) to expand search

Specification Search

Actual product appearance may vary.

Features

Environmentproof sealing
1,2, and 4 pole circuitry
Standard and pull-to-unlock levers
2 and 3 position, maintained and
momentary toggle action
Temperature range:-85? F to +160? F
Completely sealed switching chamber
Step-design case provides added
space between terminals to help
prevent shorting
UL recognized, CSA certified
CE approved

Potential Applications

Industrial machinery and equipment
Military and commercial aviation
Construction equipment
Test instruments
Agricultural machinery
Process control
Medical instrumentation

Description

MICRO SWITCH™TL Series toggle switches have high strength, temperature resistant, non-tracking case material and silver cadmium oxide contacts. Pułto-Unlock toggle levers prevent accidental operation; the lever must be pulled approx. 2,3 mm (0.09 inches) to change positions.

Supporting Documentation

Accessory: Seals

Accessory: Nuts

Engineering Drawing

Product Specifications			
Circuitry/Operating action	Keyway Position 1 2 3 6 5 4 ON	Center Position 1 2 3 6 5 4 OFF	Opposite Keyway Position 1 2 3 6 5 4 ON
Product Type	MICRO SWITCH™	Toggle Switch	
Lever Lock	Locked out of extreme position (Opposite keyway)		
Ampere/Voltage Range (Resistive Load)	0.5 A to 20 A at 0.5 Vdc to 28 Vdc,0.5 A to 15 A at 0.5 Vac to 277 Vac,0.75 A at 115 Vdc,0.5 A at 250 Vdc		
Circuitry	DPDT		
Action	3 position		
Mounting	Bushing 15/32 in		
Termination	Screw		
Lever Type	Locking		
Comment	Bright finished mounting nuts		
Availability	Global		
UNSPSC Code	30211908		
UNSPSC Commodity	30211908 Toggle sv	vitches	
Series Name	TL		