


# **Honeywell Sensing and Control**

Home> Products > MICRO SWITCH™ Toggle Switches > TL > Product Page

## Order Product and **Get Support**

- U.S. Authorized Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback

### 2TL11-515K



position, Screw terminal, Locking

TL Series Toggle Switch, 2 pole, 3



Product Search Part number search: Use (\*) to expand search **Specification Search** 

#### **Features**

Environmentproof sealing 1,2, and 4 pole circuitry Standard and pull-to-unlock levers 2 and 3 position, maintained and momentary toggle action Temperature range:-85? F to +160? F Completely sealed switching chamber Step-design case provides added space between terminals to help prevent shorting UL recognized, CSA certified CE approved

Actual product appearance may vary.

# **Potential Applications**

Industrial machinery and equipment Military and commercial aviation Construction equipment Test instruments Agricultural machinery Process control Medical instrumentation

#### **Description**

MICRO SWITCH™TL Series toggle switches have high strength, temperature resistant, non-tracking case material and silver cadmium oxide contacts. Pulto-Unlock toggle levers prevent accidental operation; the lever must be pulled approx. 2,3 mm (0.09 inches) to change positions.

# **Supporting Documentation**

Accessory: Seals

Accessory: Nuts

Engineering **Drawing** 

Product Specifications	
Circuitry/Operating action	Keyway Center Keyway Maintained Position Position Position Position  1 2 3 1 2 3 1 2 3 6 5 4 6 5 4
Product Type	MICRO SWITCH™ Toggle Switch
Lever Lock	Locked in center and extreme position (Opposite keyway)
Ampere/Voltage Range (Resistive Load)	0.75 A at 115 Vdc,0.5 A to 10 A at 0.5 Vac to 277 Vac,0.5 A to 18 A at 0.5 Vdc to 28 Vdc,0.5 A at 250 Vdc
Circuitry	DPDT
Action	3 position
Mounting	Bushing 15/32 in
Termination	Screw
Lever Type	Locking
Comment	Bright finished mounting nuts
Availability	Global
UNSPSC Code	30211908
UNSPSC Commodity	30211908 Toggle switches
Series Name	TL