




Home➤ Products > MICRO SWITCH™ Toggle Switches> TL > Product Page

2TL143-21K



Actual product appearance may vary.

TL Series Toggle Switch, 2 pole, 3 position, Screw terminal, Locking Lever

Features

- Environmentproof sealing
- 1,2, and 4 pole circuitry
- Standard and pull-to-unlock levers
- 2 and 3 position, maintained and momentary toggle action
- Temperature range:-85° F to +160° F
- Completely sealed switching chamber
- Step-design case provides added space between terminals to help prevent shorting
- UL recognized, CSA certified
- CE approved

Description

MICRO SWITCH™TL Series toggle switches have high strength, temperature resistant, non-tracking case material and silver cadmium oxide contacts. Pull-to-Unlock toggle levers prevent accidental operation; the lever must be pulled approx. 2,3 mm (0.09 inches) to change positions.

Potential Applications


- Industrial machinery and equipment
- Military and commercial aviation
- Construction equipment
- Test instruments
- Agricultural machinery
- Process control
- Medical instrumentation

Supporting Documentation

 [Accessory: Seals](#)

 [Accessory: Nuts](#)

 [Engineering Drawing](#)

Product Specifications		
Circuitry/Operating action	Center Maintained Position  Opposite Maintained Keyway Position 	
Product Type	MICRO SWITCH™ Toggle Switch	
Lever Lock	 Locked in center and extreme position (Opposite keyway)	
Ampere/Voltage Range (Resistive Load)	0.5 A to 20 A at 0.5 Vdc to 28 Vdc,0.75 A at 115 Vdc,0.5 A at 250 Vdc,0.5 A to 15 A at 0.5 Vac to 277 Vac	
Circuitry	DPST	
Action	3 position	
Mounting	Bushing 15/32 in	
Termination	Screw	
Lever Type	Locking	
UL/CSA Rating Code	L191: 15 A - 125, 250, 277 Vac; 1/2 Hp - 125 Vac; 1 Hp - 250, 277 Vac; 5 A - 120 Vac "L"	
Comment	Hex shaped button on actuator furnished unassembled	
Availability	Global	
UNSPSC Code	30211908	
UNSPSC Commodity	30211908 Toggle switches	
Series Name	TL	

Keyword Search

Search for product and support information.

All Sensing and Control▼

Product Search

Part number search:

Use (*) to expand search

Specification Search