



2TL204-7



Features

Potential Applications

Description

MICRO SWITCH™TL Series toggle switches have high strength, temperature resistant, non-tracking case material and silver cadmium oxide contacts. Pull-to-Unlock toggle levers prevent accidental operation; the lever must be pulled approx. 2,3 mm (0.09 inches) to change positions.

Supporting Documentation

 **Accessory: Lever Sleeve**

Accessory: Seals

 Accessory: Nuts

 **Engineering
Drawing**

Product Specifications		
Circuitry/Operating action	Keyway Momentary Position Center Position Opposite Keyway Momentary Position	
Product Type	MICRO SWITCH™ Toggle Switch	
Ampere/Voltage Range (Resistive Load)	0.75 A at 115 Vdc, 0.5 A at 250 Vdc, 0.5 A to 18 A at 0.5 Vdc to 28 Vdc, 0.5 A to 10 A at 0.5 Vac to 277 Vac	
Circuitry	DPDT	
Action	3 position	
Mounting	Bushing 15/32 in	
Termination	Screw	
Lever Type	Tab	
UL/CSA Rating Code	L192: 10 A - 125, 250, 277 Vac; 1/4 Hp - 250, 277 Vac; 3 A - 125 Vac "L"	- 125 Vac; 1/2
Comment	Lever 1.5" above bushing	
Availability	Global	
UNSPSC Code	30211908	
UNSPSC Commodity	30211908 Toggle switches	
Series Name	TL	