


# **Honeywell Sensing and Control**

Home> Products > MICRO SWITCH™ Toggle Switches > TL > Product Page

### Order Product and **Get Support**

- U.S. Authorized **Distributors**
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback

## 2TL51-5



TL Series Toggle Switch, 2 pole, 3 position, Screw terminal, Tab Lever

**Keyword Search** Search for product and support information. All Sensing and Contro Product Search

Part number search:

Use (\*) to expand search

**Specification Search** 

#### **Features**

Environmentproof sealing 1,2, and 4 pole circuitry Standard and pull-to-unlock levers 2 and 3 position, maintained and momentary toggle action Temperature range: -85? F to +160? F Completely sealed switching chamber Step-design case provides added space between terminals to help prevent shorting UL recognized, CSA certified CE approved

Actual product appearance may vary.

# **Potential Applications**

Industrial machinery and equipment Military and commercial aviation Construction equipment Test instruments Agricultural machinery Process control Medical instrumentation

### **Description**

MICRO SWITCH™TL Series toggle switches have high strength, temperature resistant, non-tracking case material and silver cadmium oxide contacts. Pulto-Unlock toggle levers prevent accidental operation; the lever must be pulled approx. 2,3 mm (0.09 inches) to change positions.

# **Supporting Documentation**

Accessory: Lever Sleeve Engineering

Accessory: Seals

Accessory: Nuts

Drawing	
Product Specifications	
Circuitry/Operating action	Keyway Momentary Center Position Position Position Position Position  1 2 3 1 2 3 1 2 3 6 5 4 6 5 4 6 5 4 ON OFF
Product Type	MICRO SWITCH™ Toggle Switch
Ampere/Voltage Range (Resistive Load)	0.5 A to 18 A at 0.5 Vdc to 28 Vdc,0.5 A to 10 A at 0.5 Vac to 277 Vac,0.5 A at 250 Vdc,0.75 A at 115 Vdc
Circuitry	DPDT
Action	3 position
Mounting	Bushing 15/32 in
Termination	Screw
Lever Type	Tab
UL/CSA Rating Code	L192: 10 A - 125, 250, 277 Vac; 1/4 Hp - 125 Vac; 1/2 Hp - 250, 277 Vac; 3 A - 125 Vac "L"
Comment	Rectangular white plastic lever

Global

TL

30211908

30211908 Toggle switches

Availability

UNSPSC Code

Series Name

**UNSPSC** Commodity