


# **Honeywell Sensing and Control**

Home> Products > MICRO SWITCH™ Toggle Switches > NT > Product Page

## Order Product and Get Support

- U.S. Authorized Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback

#### 31NT391-1-B02



NT Series Toggle Switch, 1 pole, 3 position, Quick Connect terminal, Tab Lever

Actual product appearance may vary.

#### **Features**

Completely sealed switching chamber NEMA 3, 3R, 4, and 13 UL recognized, File E12252, Vol. 1, Section 44 CSA certified, File LR4442 CE approved

#### **Potential Applications**

Aerial lifts, scissor lifts, truck mounted tele-handlers, and cranes
Construction equipment
Agriculture equipment
Material-handling equipment
Factory-floor control units
Machine tool equipment manufacturers

## Description

MICRO SWITCH™ NT Series toggle switches meet the need for a rugged, cost effective toggle switch. Quality construction features include a seal between the toggle lever and bushing, and between the cover and case. These switches can be used where panels are subject to splashes, hosedowns, or outdoor environments. The "Easy-Start" threaded bushing enables quick alignment of mounting nut to decrease the chance of cross threading. The panel stand-off with O-ring feature available on some listings, eliminates the need for behindhe-panel hardware, provides uniform panel height, and provides a panel to cover seal.

### **Supporting Documentation**

Accessory: Seals

Accessory: Nuts

Engineering Drawing

Product Specifications			
Circuitry/Operating action	Keyway Position	Center Position	Opposite Keyway Position
	1 2 3 ON	1 2 3 OFF	1 2 3 ON
Product Type	MICRO SWITCH™ Toggle Switch		
Ampere/Voltage Range (Resistive Load)	0.5 A to 20 A at 0.5 Vdc to 28 Vdc,0.75 A at 115 Vdc,0.5 A at 250 Vdc,0.5 A to 15 A at 0.5 Vac to 277 Vac		
Circuitry	SPDT		
Action	3 position		
Mounting	Bushing 15/32 in		
Termination	Quick Connect		
Lever Type	Tab		
UL/CSA Rating Code	L191: 15 A - 125, 250, 277 Vac; 1/2 Hp - 125 Vac; 1 Hp - 250, 277 Vac; 5 A - 120 Vac "L"		
Comment	Black		
Availability	Global		
UNSPSC Code	30211908		
UNSPSC Commodity	30211908 Toggle switches		
Series Name	NT		



Login to iCOM Login as Rep/AD Login as Guest Login to Digital University

## Keyword Search

Search for product and support information.

All Sensing and Contro

#### Product Search

Part number search:

Use (\*) to expand search

**Specification Search**