


### **Honeywell Sensing and Control**

 $Home \gt{Products} \gt{MICRO} \ SWITCH^{TM} \ Toggle \ Switches \gt{NT} \gt{Product} \ Page$ 

# Order Product and Get Support

- U.S. Authorized Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback

### 32NT391-12-C08



NT Series Toggle Switch, 2 pole, 3 position, Quick Connect terminal, Special Design Lever

Actual product appearance may vary.

#### **Features**

Completely sealed switching chamber NEMA 3, 3R, 4, and 13 UL recognized, File E12252, Vol. 1, Section 44 CSA certified, File LR4442 CE approved

### **Potential Applications**

Aerial lifts, scissor lifts, truck mounted tele-handlers, and cranes
Construction equipment
Agriculture equipment
Material-handling equipment
Factory-floor control units
Machine tool equipment manufacturers

# Description

MICRO SWITCH™ NT Series toggle switches meet the need for a rugged, cost effective toggle switch. Quality construction features include a seal between the toggle lever and bushing, and between the cover and case. These switches can be used where panels are subject to splashes, hosedowns, or outdoor environments. The "Easy-Start" threaded bushing enables quick alignment of mounting nut to decrease the chance of cross threading. The panel stand-off with O-ring feature available on some listings, eliminates the need for behindhe-panel hardware, provides uniform panel height, and provides a panel to cover seal.

### **Supporting Documentation**

Accessory: Seals

Accessory: Nuts

Engineering Drawing

Product Specifications			
Circuitry/Operating action	Keyway Maintained Position 3 2 1 6 5 4 ON	Center Maintained Position 3 2 1 6 5 4 ON	Opposite Keyway Maintained Position  3 2 1  6 5 4  ON
Product Type	MICRO SWITCH™ Toggle Switch		
Ampere/Voltage Range (Resistive Load)	0.75 A at 115 Vdc,0.5 A at 250 Vdc,0.5 A to 15 A at 0.5 Vdc to 28 Vdc,0.5 A to 10 A at 0.5 Vac to 7 Vac		
Circuitry	DPDT		
Action	3 position		
Mounting	Bushing 15/32 in		
Termination	Quick Connect		
Lever Type	Special Design		
UL/CSA Rating Code	L191: 15 A -125, 2 Hp - 250, 277 Vac; 5	250, 277 Vac; 1/2 Hp A -120 Vac "L"	-125 Vac; 1
Comment	Yellow		
Availability	Global		
UNSPSC Code	30211908		
UNSPSC Commodity	30211908 Toggle switches		
Series Name	NT		

### My Links

Login to iCOM Login as Rep/AD Login as Guest Login to Digital University

### **Keyword Search**

Search for product and support information.

All Sensing and Contro

## Product Search

Part number search:

Use (\*) to expand search

**Specification Search**