


Honeywell Sensing and Control

Home> Products > MICRO SWITCH™ Toggle Switches > NT > Product Page

Order Product and **Get Support**

- U.S. Authorized **Distributors**
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback

32NT392-12-C08



NT Series Toggle Switch, 2 pole, 3 position, Quick Connect terminal, **Special Design Lever**

Actual product appearance may vary.

Features

Completely sealed switching chamber NEMA 3, 3R, 4, and 13 UL recognized, File E12252, Vol. 1, Section 44 CSA certified, File LR4442 CE approved

Aerial lifts, scissor lifts, truck mounted tele-handlers, and cranes Construction equipment Agriculture equipment Material-handling equipment Factory-floor control units Machine tool equipment manufacturers

Potential Applications

Use (*) to expand search

Specification Search

Part number search:

My Links

Login to iCOM Login as Rep/AD

Login as Guest

Login to Digital University

Search for product and

All Sensing and Contro

support information.

Keyword Search

Product Search

Description

MICRO SWITCH™ NT Series toggle switches meet the need for a rugged, cosŧ effective toggle switch. Quality construction features include a seal between the toggle lever and bushing, and between the cover and case. These switches can be used where panels are subject to splashes, hosedowns, or outdoor environments. The "Easy-Start" threaded bushing enables quick alignment of mounting nut to decrease the chance of cross threading. The panel stand-off with O-ring feature available on some listings, eliminates the need for behindhe-panel hardware, provides uniform panel height, and provides a panel to cover seal.

Supporting Documentation

Accessory: Seals

Accessory: Nuts

Product Specifications			
Circuitry/Operating action	Keyway Maintained Position 3 2 1 6 5 4 ON	Center Maintained Position 3 2 1 6 5 4 ON	Opposite Keyway Maintained Position 3 2 1 6 5 4 ON
Product Type	MICRO SWITCH™ Toggle Switch		
Ampere/Voltage Range (Resistive Load)	0.75 A at 115 Vdc,0.5 A at 250 Vdc,0.5 A to 15 A at 0.5 Vdc to 28 Vdc,0.5 A to 10 A at 0.5 Vac to 7 Vac		
Circuitry	DPDT		
Action	3 position		
Mounting	Bushing 15/32 in		
Termination	Quick Connect		
Lever Type	Special Design		
UL/CSA Rating Code	L191: 15 A - 125, 250, 277 Vac; 1/2 Hp - 125 Vac; 1 Hp - 250, 277 Vac; 5 A - 120 Vac "L"		
Comment	Yellow		
Availability	Global		
UNSPSC Code	30211908		
UNSPSC Commodity	30211908 Toggle switches		
Series Name	NT		