


# **Honeywell Sensing and Control**

Home> Products > MICRO SWITCH™ Toggle Switches > NT > Product Page

### ■ Order Product and **Get Support**

- U.S. Authorized Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback

## 32NT392-6-C08



NT Series Toggle Switch, 2 pole, 2 position, Quick Connect terminal, Tab Lever

Actual product appearance may vary.

### **Features**

Completely sealed switching chamber NEMA 3, 3R, 4, and 13 UL recognized, File E12252, Vol. 1, Section 44 CSA certified, File LR4442 CE approved

Aerial lifts, scissor lifts, truck mounted tele-handlers, and cranes Construction equipment Agriculture equipment Material-handling equipment Factory-floor control units Machine tool equipment manufacturers

### **Potential Applications**

# Part number search:

My Links

Login to iCOM Login as Rep/AD

Login as Guest

**Login to Digital** University

Search for product and

All Sensing and Contro

support information.

**Keyword Search** 

Product Search

Use (\*) to expand search

**Specification Search** 

### **Description**

MICRO SWITCH™ NT Series toggle switches meet the need for a rugged, cost effective toggle switch. Quality construction features include a seal between the toggle lever and bushing, and between the cover and case. These switches can be used where panels are subject to splashes, hosedowns, or outdoor environments. The "Easy Start" threaded bushing enables quick alignment of mounting nut to decrease the chance of cross threading. The panel standoff with O-ring feature available on some listings, eliminates the need for behindhe-panel hardware, provides uniform panel height, and provides a panel to cover seal.

### **Supporting Documentation**

Accessory: Seals

Accessory: Nuts

Engineering **Drawing** 

	_
Product Specifications	
Circuitry/Operating action	Keyway Opposite Momentary Keyway Position Position 1 2 1 2
Product Type	5 4 5 4 OFF  MICRO SWITCH™ Toggle Switch
Ampere/Voltage Range (Resistive Load)	0.5 A at 250 Vdc,0.75 A at 115 Vdc,0.5 A to 10 A at 0.5 Vac to 277 Vac,0.5 A to 18 A at 0.5 Vdc to 28 Vdc
Circuitry	DPST
Action	2 position
Mounting	Bushing 15/32 in
Termination	Quick Connect
Lever Type	Tab
UL/CSA Rating Code	L192: 10 A - 125, 250, 277 Vac; 1/4 Hp - 125 Vac; 1/2 Hp - 250, 277 Vac; 3 A - 125 Vac "L"
Comment	Yellow
Availability	Global
UNSPSC Code	30211908
UNSPSC Commodity	30211908 Toggle switches
Series Name	NT