




Order Product and Get Support

- U.S. Authorized Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback

41CX4



Actual product appearance may vary.

Explosion-Proof Limit Switches Series
CX: Standard Housing: Top Plunger;
1NC 1NO SPDT Snap Action; Number of
internal basic switches BZ: 4; 0.75 in -
14NPT conduit

Features

Sealing- applicable portions of NEMA 1, 3, 4, 4X, 6, 6P, 7, 9, and 13
Watertight and dust-tight for outdoor use
4 mA to 20 mA analog output available
UL Listed, file #E14274
Analog UL file #E68247
CSA Certified, file #LR57324
Rugged, cast aluminum housing
Pretravel, overtravel, and actuating sequence can be field adjusted without tools (all basics individually)
Rotary types convert in seconds to clockwise, counter -clockwise, or both - way operation

Potential Applications

Control valves and actuators
Petro-chemical plants
Grain handling
Waste treatment
Hazardous waste handing
Power generating
Paint facilities

Description

MICRO SWITCH™ CX switches are built especially for outdoor use in hazardous atmospheres. These enclosures are constructed to withstand the pressure of an internal explosion. Flame paths cool the exploded gases to a point less than the lowest safe operating temperature of the surrounding gas.

Supporting Documentation

 [Installation Instructions](#)

 [Engineering Drawing](#)

Product Specifications	
Availability	Global
Operating Force (O.F.)	4,0 Kg [8.82 lb] max.
Pretravel (P.T.)	2,5 mm max. [0.1 in max.]
Overtravel (O.T.)	4,75 mm min. [0.187 in min.]
Differential Travel (D.T.)	1.0 mm [0.04 in] max.
Product Type	MICRO SWITCH™ Weather - Sealed, Explosion - Proof Limit Switches
Actuator	Plunger
Circuitry	1NC 1NO SPDT Snap Action; 4 Basic Switches
Ampere Rating	15 A Ind./ 0.5 A Res./0.25 A Res.
Supply Voltage	120 Vac, 240 Vac or 480 Vac/125 Vdc/250 Vdc
Housing Material	Aluminum
Termination Type	0.75 in - 14NPT conduit
Housing Type	CX: Standard: 145 mm [5.71 in]
Series Name	CX
Sealing	NEMA 1, 3, 4, 4x, 6, 6P, 7 (Class I, Division 1, Groups C, D), 9 (Class II, Division 1, Groups E, F,G), 13
Approvals	UL listed, CSA Certified
CSA File #	LR57324
UL File #	E14274
Operating Temperature Range	-25 °C to 85 °C [-13 °F to 185 °F]
UNSPSC Code	302119
UNSPSC Commodity	302119 Switches and controls and relays
Sealed	Explosion - proof

My Links

[Login to iCOM](#)
[Login as Rep/AD](#)
[Login as Guest](#)
[Login to Digital University](#)

Keyword Search

Search for product and support information.

All Sensing and Control

Product Search

Part number search:

Use (*) to expand search

Specification Search