H ABOUTUS ▼

## 11TW1-3

Products > Switches > Toggle Switches > TW Series > 11TW1-3

TW

0.1 A to 5.0 A

at 0.5 Vdc to

28 Vdc|0.1 A

to 5.0 A at

0.5 Vac to

2 position

**Bushing** 

15/32 in

23-1

MS27718-

115 Vac

**Product Type** 

Circuitry/Operating

View documents in: English

Circuitry

action

Termination

Lever Type

#### Overview

MICRO SWITCH TW Series Toggle Switch, 1 pole, 2 position, Solder terminal, Standard Lever, Military Part Number MS27718-23-1....

View More

**Technical Specifications** 

Series Name

Range

Action

Mounting

MIL Spec. Number

Ampere/Voltage

(Resistive Load)



**MICRO** 

**SWITCH** 

Toggle

Switch

**SPDT** 

ON

Solder

Standard



riew all 11TW1-3	
literature	
_	













View More

## **Documents**

DOCUMENT LANGUAGE SIZE TITLE **TYPE** Photo 11TW1-3 highres photo 2MB English 🛼 11TW1-3 lowres photo Photo English 74KB MICRO SWITCH TW Series Miniature Military-Grade Datasheet English 1MB **Toggle Switches** 🔜 Sensors and Switches in Oil **Application** English 7MB Rig Applications Note

View More

#### **Product Features**

- Qualified to MIL-DTL-83731
- Save space and weight
- SPDT and DPDT circuitry
- Temperature range: -65 °C to 71 °C [-85 °F to 160 °F]
- Sealed bushing versions
- Choice of 1/4 in or 15/32 in bushing
- Color tab available on 15/32 in. bushing
- UL recognized



# **Applications**

- Industrial machinery and equipment
- Military and commercial aviation
- Construction equipment
- Test instruments
- Agricultural machinery
- Process control
- Medical instrumentation

NAVIGATION LINKS

HOME PAGE

PRODUCTS

DISTRIBUTOR INVENTORY

INDUSTRIES SUPPORT

NEWS & EVENTS

ABOUT US

DISTRIBUTOR LINKS

ECOM LOGIN

LEARN CENTER

REQUEST ACCESS TO ECOM

SALES/AD PORTAL LOGIN

SALES/AD PORTAL ACCESS REQUEST

SAMPLE REQUEST

SUPPLIER MICROSITE

LANGUAGE



SOCIAL MEDIA



SITE INFORMATION

PRIVACY STATEMENT

SITEMAP

TERMS & CONDITIONS

COPYRIGHT © 2018 HONEYWELL INTERNATIONAL INC.