

BZ-2R55

(Home : Products : Switches : MICRO SWITCH™ Basic Switches : Premium Large Basic Switches : BZ/BA/WA/YZ)

Actual product
appearance may vary.BZ Series Standard Basic Switch, Single Pole Double Throw Circuitry, N/A at 250
Vac, Pin Plunger Actuator, Solder Termination, Silver Contacts, UL, CSA, ENEC[click here to download Hi-Res image](#)

Distributor Inventory

Input part number for stock availability

Narrow Your Search**Modify Your Search****Products****Technology****Industries Served**

Sales & Service

Distributor Inventory

Overview

Specs

Documentation

Application Notes

Product Specifications

Switch Type	MICRO SWITCH™ Standard 25,4 mm H x 17,8 mm W x 50,8 mm L [1.0 in H x 0.7 in W x 2.0 in L]
Sealed	Environmentally
Circuitry	SPDT
Actuator	Pin Plunger
Termination	Solder
Operating Temperature	-55 °C to 85 °C [-67 °F to 185 °F]
Voltage	250 Vac
Contact Type	Silver
Material	Plastic
Housing Material	General Purpose Phenolic
Agency Approvals and Standards	UL, CSA, ENEC
Mounting Screw Size	3,53 mm [0.139 in]
Mounting Centers	25,4 mm [1 in]
Tightening Torque	0,33 N m [3.0 in lb]
Weight	24,94 g to 34,01 g [0.055 lb to 0.075 lb]
Package Height	24,1 mm [0.95 in]
Package Width	17,5 mm [0.69 in]
Package Length	49,3 mm [1.94 in]
Availability	Global
UNSPSC Code	30211905
UNSPSC Commodity	30211905 Snap switches
Series Name	BZ/BA/WA/YZ

Product SearchProduct Type: ☐ New Products OnlyIndustry: ☒ Entire Product CatalogSearch Term: **Search****My Links**[eCOM Login](#)
[Request Access to eCOM](#)
[Rep/AD Portal Login](#)**Literature and Media**[Data Sheets](#)
[Videos](#)
[Literature](#)**Contacts**[Customer Service](#)
[Technical Support](#)
[Global Sales & Service](#)

[Rep/AD Portal Access Request](#)
[Sample Request](#)
[Digital University Login](#)
[Limitless Microsite](#)
[Supplier Microsite](#)

[Literature Request](#)
[White Papers](#)
[Application Notes](#)
[Application Demos](#)

[Website Feedback](#)



[Terms & Conditions](#)

[Privacy Statement](#)

[Site Map](#)