



12TW8-10A

(Home : Products : Switches : MICRO SWITCH™ Toggle Switches : TW)



TW Series Toggle Switch, 2 pole, 3 position, Solder terminal, Locking Lever

Actual product appearance may vary.

Sales & Service

Distributor Inventory

Distributor Inventory

Input part number for stock availability

Narrow Your Search

Modify Your Search

Products

Select Option

Technology

Select Option

Industries Served

Select Option

Overview

Specs

Documentation

Description

MICRO SWITCH™ miniature toggle switches in two bushing sizes. Molded-in terminals are plated for soldering. Momentary and maintained circuitry closures available. Special on-on-on circuitries are also available. Pull-to-unlock levers prevent accidental operation.

Features

- Save space and weight
- SPDT and DPDT circuitry
- Temperature range: -85°F to +160°F (-65°C to +71°C)
- Sealed bushing versions
- Choice of 1/8 in. or 15/32 in. bushing
- Color tab available on 15/32 in. bushing
- UL recognized

Potential Applications

- Industrial machinery and equipment
- Military and commercial aviation
- Construction equipment
- Test instruments
- Agricultural machinery
- Process control
- Medical instrumentation

Product Search

Product Type: All Product Types

☐ New Products Only

Industry: All Industries

☒ Entire Product Catalog

Search Term: Start Here ...

Search

My Links

- » eCOM Login
- » Request Access to eCOM
- » Rep/AD Portal Login
- » Rep/AD Portal Access Request
- » Sample Request
- » Digital U - HVL Learning Hub Login
- » Limitless Microsite
- » Supplier Microsite

Literature and Media

- » Data Sheets
- » Videos
- » Literature
- » Literature Request
- » White Papers
- » Application Notes
- » Application Demos
- » CAD Renderings

Contacts

- » Customer Service
- » Technical Support
- » Global Sales & Service