



NL2FX

2 pole cable connector, chuck type strain relief

The industry-standard for loudspeaker connections offer extremely reliable and robust cable connectors with a reliable locking system. They feature solid contacts with screw-type terminals including a stranded wire protection which offer also solder termination.

Features & Benefits

- Current rating 40 A continuous, 50 A audio signal with 50% duty cycle
- High impact materials – long-lasting and reliable
- 1 piece strain relief, chuck for 6 to 10 mm cable O.D.
- Mates with 4-pole chassis connector as well and makes contact with +1/-1
- Only 3 parts, easy to assemble
- Easy and extremely precise locking system "Quick Lock"
- Improved grip on latch

Technical Information

Product	
Title	NL2FX
Connection Type	speakON
Gender	female

Electrical	
Contact resistance	< 2 mΩ (after lifetime)
Dielectric strength	4 kVdc (peak)
Insulation resistance	> 1 GΩ (after dampheat)
Rated current per contact	40 A rms continuous
Rated current per contact	50 A audiosignal, duty cycle 50 %
Rated voltage	250 V ac
Attention	speakON is not to be used as an AC mains or power supply connector!

Mechanical	
Cable O.D.	6 - 10 mm
Cable retention	≥ 220 N (subject to cable O.D. and material)
Lifetime	> 5000 mating cycles
Wiresize	1.5 - 4 mm ²
Wiresize	16 - 12 AWG
Wiring	screw type terminals or soldering
Locking device	Quick Lock (latch)

Material	
Contact plating	4 μm Ag
Contacts	Brass (CuZn39Pb3)
Insert	PBTP 20 % GR
Locking element	Zinc diecast (ZnAl4Cu1)
Shell	PBTP 20 % GR
Strain relief	Polyacetal (POM)

Environmental	
Flammability	UL 94 HB
Solderability	Complies with IEC 68-2-20
Temperature range	-30 °C to +80 °C