

[Home](#)
[About Us](#)[Products](#)[Audio](#)[Video](#)[Lighting](#)[Data Connectors](#)[Industrial](#)[Support](#)[News](#)[Sitemap](#)

Search

☐ PRODUCTS
ONLY


Search

© Neutrik® AG
All rights reserved
Legal Notices

P Series

[back](#)

NC3FP-BAG-1



Product

Connector Type	XLR
Gender	female

Electrical

Capacitance between contacts	≤ 4 pF
Contact resistance	≤ 5 m Ω
Dielectric strength	1,5 kVdc
Insulation resistance	> 2 G Ω (initial)
Insulation resistance	> 1 G Ω (after damp heat test)
Rated current per contact	16 A
Rated voltage	50 V

Mechanical

Insertion force	≤ 20 N
Withdrawal force	≤ 20 N
Lifetime	> 1000 mating cycles
Wiring	Solder contacts
Locking device	Latch lock
Mounting direction	front
Chassis shape	P

Material

Contact plating	2 μ m Ag over 2 μ m Ni
Contacts	Bronze (CuSn6)
Insert	Polyamide (PA 6.6 30 % GR)
Locking element	Steel Ck67
Shell	Zinc diecast (ZnAl4Cu1)
Shell plating	Black chromium

Environmental

Flammability	UL 94 HB
Standard compliance	IEC 61076-2-103
Protection class	IP 40
Solderability	Complies with IEC 68-2-20
Temperature range	-30 °C to +80 °C