

G3VM-41PR5

MOS FET Relays

Smallest 40V MOS FET Relay In The Market (USOP Package Size); Designed to exhibit Low Output Capacitance and On Resistance ($C_xR=10\text{pF}\cdot\Omega$)

- Specifically Designed to low ON Resistance 1Ω (typ.)
- Dielectric strength of 500Vrms between I/O.



NEW

Note: The actual product is marked differently from the image shown here.

RoHS Compliant





Refer to "Common Precautions".

Application Examples

- Semiconductor test equipment
- Communication equipment
- Test & measurement equipment
- Data loggers

Terminal Arrangement/Internal Connections



Note: The actual product is marked differently from the image shown here.

List of Models

Package type	Contact form	Terminals	Load voltage (peak value) *	Model	Minimum package quantity
					Number per tape & reel
USOP4	1a (SPST-NO)	Surface-mounting terminals	40V	G3VM-41PR5	—
				G3VM-41PR5 (TR05)	500

* The AC peak and DC value are given for the load voltage.

Absolute Maximum Ratings ($T_a = 25^\circ\text{C}$)


Item		Symbol	Rating	Unit	Measurement conditions
Input	LED forward current	I_F	50	mA	$T_a \geq 25^\circ\text{C}$
	LED forward current reduction rate	$\Delta I_F / ^\circ\text{C}$	-0.5	$\text{mA}/^\circ\text{C}$	
	LED reverse voltage	V_R	5	V	
	Connection temperature	T_J	125	$^\circ\text{C}$	
Output	Load voltage (AC peak/DC)	V_{OFF}	40	V	$T_a \geq 25^\circ\text{C}$
	Continuous load current (AC peak/DC)	I_o	300	mA	
	ON current reduction rate	$\Delta I_o / ^\circ\text{C}$	-3	$\text{mA}/^\circ\text{C}$	
	Pulse ON current	I_{op}	900	mA	
	Connection temperature	T_J	125	$^\circ\text{C}$	
Dielectric strength between I/O (See note 1.)		V_{I-O}	500	Vrms	AC for 1 min
Ambient operating temperature		T_a	-40~+85	$^\circ\text{C}$	With no icing or condensation
Ambient storage temperature		T_{stg}	-40~+125	$^\circ\text{C}$	With no icing or condensation
Soldering temperature		—	260	$^\circ\text{C}$	10s

Note: 1. The dielectric strength between the input and output was checked by applying voltage between all pins as a group on the LED side and all pins as a group on the light-receiving side.

Electrical Characteristics ($T_a = 25^\circ\text{C}$)

Item		Symbol	Minimum	Typical	Maximum	Unit	Measurement conditions
Input	LED forward voltage	V_F	1	1.15	1.3	V	$I_F=10\text{mA}$
	Reverse current	I_R	—	—	10	μA	$V_R=5\text{V}$
	Capacity between terminals	C_T	—	15	—	pF	$V=0, f=1\text{MHz}$
	Trigger LED forward current	I_{FT}	—	0.6	3	mA	$I_o=100\text{mA}$
Output	Maximum resistance with output ON	R_{ON}	—	1	1.5	Ω	$I_F=5\text{mA}, I_o=300\text{mA}, t<1\text{s}$
	Current leakage when the relay is open	I_{LEAK}	—	—	1	nA	$V_{OFF}=40\text{V}$
	Capacity between terminals	C_{OFF}	—	10	14	pF	$V=0, f=100\text{MHz}, t<1\text{s}$
	Capacity between I/O terminals	C_{I-O}	—	0.4	—	pF	$f=1\text{MHz}, V_s=0\text{V}$
	Insulation resistance between I/O terminals	R_{I-O}	1000	—	—	$\text{M}\Omega$	$V_{I-O}=500\text{VDC}, R_oH \leq 60\%$
Turn-ON time		t_{ON}	—	0.2	0.5	ms	$I_F=5\text{mA}, R_L=200\Omega, V_{DD}=20\text{V}$ (See note 2.)
Turn-OFF time		t_{OFF}	—	0.2	0.3	ms	

Note: 2. Turn-ON and Turn-OFF Times




Recommended Operating Conditions

Use the G3VM under the following conditions so that the Relay will operate properly.


Item	Symbol	Minimum	Typical	Maximum	Unit
Load voltage (AC peak/DC)	V_{DD}	—	—	32	V
Operating LED forward current	I_F	5	7.5	20	mA
Continuous load current (AC peak/DC)	I_O	—	—	300	mA
Ambient operating temperature	T_a	-20	—	65	°C

Engineering Data


LED forward current vs. Ambient temperature




Continuous load current vs. Ambient temperature




LED forward current vs. LED forward voltage




Continuous load current vs. On-state voltage




On-state resistance vs. Ambient temperature




Trigger LED forward current vs. Ambient temperature




Turn ON, Turn OFF time vs. LED forward current




Turn ON, Turn OFF time vs. Ambient temperature



Current leakage vs. Load voltage



Output terminal capacitance COFF/COFF(0v) vs. Load voltage




Safety Precautions

- Refer to "Common Precautions" for all G3VM models.

■Appearance

USOP (Ultra Small Outline Package)
USOP4



Note: The actual product is marked differently from the image shown here.



■Dimensions

(Unit: mm)




Surface-mounting Terminals

Weight: 0.03g



Actual Mounting Pad Dimensions

(Recommended Value, Top View)



Note: The actual product is marked differently from the image shown here.

- Application examples provided in this document are for reference only. In actual applications, confirm equipment functions and safety before using the product.
- Consult your OMRON representative before using the product under conditions which are not described in the manual or applying the product to nuclear control systems, railroad systems, aviation systems, vehicles, combustion systems, medical equipment, amusement machines, safety equipment, and other systems or equipment that may have a serious influence on lives and property if used improperly. Make sure that the ratings and performance characteristics of the product provide a margin of safety for the system or equipment, and be sure to provide the system or equipment with double safety mechanisms.

Note: Do not use this document to operate the Unit.

OMRON Corporation

ELECTRONIC AND MECHANICAL COMPONENTS COMPANY

Contact: www.omron.com/ecb

Cat. No. K201-E1-01
0114(0114)(O)