

[All Categories](#) > [Control Components](#) > [Timers](#) > [Time-Delay Relays](#) > [H3YN-B](#) > Item # H3YN-4-B DC12

Item # H3YN-4-B DC12, 0.1 s, 10 m Time Range Timer

Request Information

[Printable Page](#)

[Download PDF](#)

[Email This Page](#)



Timer 4PDT 0.1s-10min Black DC12

DOWNLOADS

[H3Y-B, H3YN-B  
Miniature Timers, Push-  
In Plus Terminal Sockets  
Datasheet](#)

Specifications

|                                        |                                      |
|----------------------------------------|--------------------------------------|
| Type                                   | Timer                                |
| Output Type                            | 4 Pole Double Throw (PDT)            |
| Time Range                             | 0.1 s, 10 min                        |
| Dependencies                           | PYF-14-PU-L                          |
| Accessories                            | PFP                                  |
| Display                                | Light Emitting Diode (LED) Indicator |
| Setting Method                         | Analog Dial                          |
| Reset Method                           | Self Reset                           |
| ON-Delay Mode                          | Yes                                  |
| Repeat Cycle OFF Start Mode            | Yes                                  |
| Repeat Cycle ON Start Mode             | Yes                                  |
| Repeat Cycle, Independent ON/OFF Times | No                                   |
| Signal ON/OFF Delay ON Start Mode      | No                                   |
| Signal ON/OFF Delay OFF Start Mode     | No                                   |
| Signal OFF Delay Mode                  | No                                   |
| Interval Mode                          | No                                   |
| One-Shot Output Mode                   | Yes                                  |

|                                           |               |
|-------------------------------------------|---------------|
| <b>Power OFF Delay</b>                    | No            |
| <b>Power ON Delay</b>                     | No            |
| <b>ON/OFF Adjustable Duty Cycle</b>       | No            |
| <b>Twin Timer</b>                         | No            |
| <b>Stopwatch</b>                          | No            |
| <b>Cumulative</b>                         | No            |
| <b>On-Delay with Instantaneous Output</b> | No            |
| <b>Star-Delta</b>                         | No            |
| <b>Inputs</b>                             | No Inputs     |
| <b>Connection Type</b>                    | 14 Pin Socket |
| <b>Direct Current (DC) Supply Voltage</b> | 12 V          |
| <b>Height</b>                             | 28 mm         |
| <b>Width</b>                              | 21.5 mm       |
| <b>Depth</b>                              | 56.6 mm       |
| <b>Number of Operating Modes</b>          | 4             |

News

- Product News
- Corporate News
- Omron on Social Media
- eNews

Company Info

- About Omron
- Omron Principles
- Company Profile
- Business Fields
- Events
- Giving Back
- Environmental

Careers

- Awards
- Giving Back
- Summer Internships

Contact

- Omron in United States
- Contact Us
- Global presence

Follow us

-  Facebook
-  Twitter
-  LinkedIn
-  Youtube