

[All Categories](#) > [Switching Components](#) > [Electromechanical Relays](#) > [Industrial Plug-in Relays](#) > [MK-S](#) > Item # MKS3PI AC120

Item # MKS3PI AC120, 60 °C Operating Temperature [Max] General Purpose Relay

Request Information

[Printable Page](#)

[Download PDF](#)

[Email This Page](#)



Reliable general-purpose relay with round pin base

DOWNLOADS

- [MKS General Purpose Relays Data Sheet](#)
- [One Stop Packaging Brochure](#)

Specifications

Type	General Purpose Relay
Terminal Type	Plug-In
Contact Configuration	3 Pole Double Throw (PDT)
Dependencies	PF113A, PF113A-E, PF113A-D
Special Function	Non-Standard Internal Connection
Indicator Operation	Mechanical
Test Button	Latching Lever Type
RoHS Compliant	Yes
Operating Temperature [Min]	-40 °C
Operating Temperature [Max]	60 °C
AC Coil Voltage	120 V
Rated Resistive Load Current at 250 VAC Voltage (Normally Open (NO))	10 A
Rated Resistive Load Current at 30 VDC Voltage (Normally Open (NO))	10 A
Rated Resistive Load Current at 250 VAC Voltage (Normally Closed (NC))	5 A
Rated Resistive Load Current at 30 VDC Voltage (Normally Closed (NC))	5 A

Rated Inductive Load Current at 250 VAC Voltage	7 A
AC Switching Voltage [Max]	250 V
DC Switching Voltage [Max]	250 V
Switching Current [Max]	10 A
Resistive Switching Power (Normally Open (NO)) [Max]	2500 V·A 300 W
Resistive Switching Power (Normally Closed (NC)) [Max]	1250 V·A 150 W
Inductive Switching Power [Max]	1750 V·A
Load at 1 VDC Voltage [Min]	10 mA
Approximate Power Consumption (60 Hz)	2.3 V·A
Approximate Power Consumption (50 Hz)	2.7 V·A

News

Product News
Corporate News
Omron on Social Media
eNews

Company Info

About Omron
Omron Principles
Company Profile
Business Fields
Events
Giving Back
Environmental

Careers

Awards
Giving Back
Summer Internships

Contact

Omron in United States
Contact Us
Global presence

Follow us

 Facebook
 Twitter
 LinkedIn
 Youtube