

[All Categories](#) > [Switching Components](#) > [Electromechanical Relays](#) > [Industrial Plug-in Relays](#) > [MK-S](#) > Item # MKS2PIN-V AC120

Item # MKS2PIN-V AC120, 60 °C Operating Temperature [Max] General Purpose Relay

Request Information

[Printable Page](#)

[Download PDF](#)

[Email This Page](#)



Reliable general-purpose relay with round pin base

DOWNLOADS

- [MKS General Purpose Relays Data Sheet](#)
- [One Stop Packaging Brochure](#)

Specifications

Type	General Purpose Relay
Terminal Type	Plug-In
Contact Configuration	Double Pole Double Throw (DPDT)
Dependencies	PF083A, PF083A-E, PF083A-D
Indicator Operation	Light Emitting Diode (LED), Mechanical
Protection Device	Varistor
Test Button	Latching Lever Type
RoHS Compliant	Yes
Operating Temperature [Min]	-25 °C
Operating Temperature [Max]	60 °C
AC Coil Voltage	120 V
Rated Resistive Load Current at 250 VAC Voltage (Normally Open (NO))	10 A
Rated Resistive Load Current at 30 VDC Voltage (Normally Open (NO))	10 A
Rated Resistive Load Current at 250 VAC Voltage (Normally Closed (NC))	5 A
Rated Resistive Load Current at 30 VDC Voltage (Normally Closed (NC))	5 A

Rated Inductive Load Current at 250 VAC Voltage	7 A
AC Switching Voltage [Max]	250 V
DC Switching Voltage [Max]	250 V
Switching Current [Max]	10 A
Resistive Switching Power (Normally Open (NO)) [Max]	2500 V·A 300 W
Resistive Switching Power (Normally Closed (NC)) [Max]	1250 V·A 150 W
Inductive Switching Power [Max]	1750 V·A
Load at 1 VDC Voltage [Min]	10 mA
Approximate Power Consumption (60 Hz)	2.3 V·A
Approximate Power Consumption (50 Hz)	2.7 V·A

News

- Product News
- Corporate News
- Omron on Social Media
- eNews

Company Info

- About Omron
- Omron Principles
- Company Profile
- Business Fields
- Events
- Giving Back
- Environmental

Careers

- Awards
- Giving Back
- Summer Internships

Contact

- Omron in United States
- Contact Us
- Global presence

Follow us

-  Facebook
-  Twitter
-  LinkedIn
-  Youtube