

Indicators

M22N-BC-TRA-RD-P

English



Print Page



Image

Assembled Parts, Cylindrical type (22 mm dia. /Ring when using: 25 mm dia.), Resin flat sculpture type, Lighted, LED lamp, Red, 100 VAC, Push-In Plus Terminal Block, IP66

Type	Indicator (Cylindrical 22-dia.)
Operating portion	Resin flat sculpture type Red
Terminal	Push-In Plus Terminal Block

[Item list of M22N](#)

Series

Indicators
M22N[Catalog](#)

about this Product

[Inquiry of this Product](#)

Ratings

As of September 9, 2016

Type	Indicator (Cylindrical 22-dia.)
Operating portion	Resin flat sculpture type Red
Lamp variation	LED lamp
Lamp ratings	100 VAC 110 VAC 120 VAC 12 mA
Lamp operating voltage	100 VAC ±10% 100 VAC±10% 100 to 130 VAC
Terminal	Push-In Plus Terminal Block
Dielectric strength	Between each terminal and ground: 2500 V
Vibration resistance (Malfunction)	10 to 55 Hz, 1.5-mm double amplitude
Shock resistance	Malfunction: 1000 m/s**2 max.
Ambient temperature range	Operating: -25 to 55 °C Storage: -40 to 80 °C
Ambient humidity range	Operating: 35 to 85 %
Degree of protection	IP66/NEMA4X/NEMA13
Degree of protection against electric shock	Class II
Tracking characteristic (PTI)	175
Pollution degree	3 (EN60947-5-1)

As of September 9, 2016

[Top of page](#)