

CRB-48-70180 Product Details



CRB-48-70180
(1393138-3)
TE Internal Number: 1393138-3
 [Active](#)
 [Add to Part List](#)

Time Delay Relays

[Not EU RoHS or ELV Compliant](#)

Product Highlights:

- CR Series
- Time Delay Relay
- Input Voltage = 120 VAC
- Contact Arrangement = 2 Form C, DPDT, 2 C/O
- Contact Rating = 10A @ 30 VDC or 277 VAC

[View all Features](#) | [Find Similar Products](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)
- [Request Samples](#)

NEW!

Documentation & Additional Information

Product Drawings:

- None Available

Catalog Pages/Data Sheets:

- [CR Recycle Time Delay Relay](#) (PDF, English)

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

Additional Information:

- [Product Line Information](#)

Additional Product Images:

- [Schematic](#)
- [Wiring Diagram](#)

Related Products:

- [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Product Type = Time Delay Relay
- Termination Type = 8-Pin Octal Style Plug

Electrical Characteristics:

- Input Voltage (VAC) = 120
- Contact Rating = 10A @ 30 VDC or 277 VAC

Body Related Features:

- [Series](#) = CR

Contact Related Features:

- Mounting Options = Socket
- Mode of Operation = Recycle Timer
- Delay Time = 1.8 seconds to 180 seconds
- Type of Control = Knob
- Repeatability, Max. = ± 2%
- Approved Standards = CSA Certified, UL Recognized
- Contact Material = Silver Cadmium Oxide
- Approx. Dimensions (L x W x H) (mm [in]) = 61.10 x 45.20 x 90.40 [2.407 x 1.780 x 3.561]
- Enclosure = White Plastic Case

Configuration Related Features:

- [Contact Arrangement](#) = 2 Form C, DPDT, 2 C/O
- Multiple Timing Ranges = Without

Industry Standards:

- [RoHS/ELV Compliance](#) = Not ELV/RoHS compliant
- [Lead Free Solder Processes](#) = Not relevant for lead free process

Conditions for Usage:

- Temperature Range (°C) = -10 - +55

Other:

- Brand = Potter & Brumfield