

## Plastic label - EMLP (EX30)R - 0802688

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Plastic label, Roll, white, unlabeled, can be labeled with: THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, THERMOMARK ROLL X1, THERMOMARK ROLL 2.0, THERMOMARK ROLL, mounting type: adhesive, lettering field size: 20000 x 30 mm, Number of individual labels: 1

### Your advantages

- ✓ The EMLP (Ex...)R ... self-adhesive continuous markers are particularly well suited to marking miniature circuit breakers and housing covers in service panels
- ✓ The markers meet the same standards as the engraved labels. They provide high-quality visuals.
- ✓ Quick and inexpensive marking with THERMOMARK ... roll printers from PHOENIX CONTACT
- ✓ The thermal transfer printer cutting units make it possible to trim precisely to the required length. This enables faster and cleaner equipment marking.
- ✓ When combined with the right ink ribbon, the marking is highly resistant to solvents and mechanical influences. The marking is even suitable for use under harsh industrial conditions.

RoHS

### Key Commercial Data

|                                      |                                                                                                         |
|--------------------------------------|---------------------------------------------------------------------------------------------------------|
| Packing unit                         | 1 pc                                                                                                    |
| GTIN                                 | <br>4 046356 791694 |
| GTIN                                 | 4046356791694                                                                                           |
| Weight per Piece (excluding packing) | 460.000 g                                                                                               |
| Custom tariff number                 | 39269092                                                                                                |
| Country of origin                    | Germany                                                                                                 |

### Technical data

#### Dimensions

|            |          |
|------------|----------|
| Length (b) | 20000 mm |
| Width (a)  | 30 mm    |

#### Ambient conditions

# Plastic label - EMLP (EX30)R - 0802688

## Technical data

### Ambient conditions

|                                 |                                                                                                         |
|---------------------------------|---------------------------------------------------------------------------------------------------------|
| Ambient temperature (operation) | -40 °C ... 120 °C                                                                                       |
| Recommended storage conditions  | 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended. |

### General

|                                                                     |                                   |
|---------------------------------------------------------------------|-----------------------------------|
| Color                                                               | white                             |
| Components                                                          | free from silicone and halogen    |
| Material                                                            | Polyester                         |
| RoHS compliant                                                      | Yes                               |
| Wipe resistance                                                     | DIN EN 61010-1 (VDE 0411-1)       |
| Number of individual labels                                         | 1                                 |
| Number of individual labels per row                                 | 1                                 |
| Adhesive                                                            | Acrylic                           |
| Printability                                                        | Thermal transfer                  |
| Device                                                              | 5146477 THERMOMARK ROLL           |
|                                                                     | 5146723 THERMOMARK ROLL X1        |
|                                                                     | 5146231 THERMOMARK X1.2           |
|                                                                     | 0804501 THERMOMARK ROLLMaster 300 |
|                                                                     | 0804663 THERMOMARK ROLLMaster 600 |
| Ink ribbon                                                          | 5145384 THERMOMARK-RIBBON 110     |
| Test for substances that would hinder coating with paint or varnish | VW PV 3.10.7:2005-02              |
| Result                                                              | Test passed                       |
| Test specification weathering-resistance                            | Following ISO 4892-2:2013-03      |
| Test duration                                                       | 96 h                              |
| Result of weather resistance test                                   | Test passed                       |
| Salt spray test specification                                       | DIN EN 60068-2-11:2000-02         |
| Test duration                                                       | 96 h                              |
| Salt spray testing result                                           | Test passed                       |
| Wipe resistance of test specification inscriptions                  | DIN EN 60068-2-11:2000-02         |
| Result of wipe resistance test                                      | Test passed                       |
| Foil strength                                                       | 50 µm                             |
| Adhesive strength                                                   | 20 µm                             |
| Marking mounting type                                               | adhesive                          |

### Standards and Regulations

|                 |                             |
|-----------------|-----------------------------|
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
|-----------------|-----------------------------|

## Plastic label - EMLP (EX30)R - 0802688

### Classifications

#### eCl@ss

|               |          |
|---------------|----------|
| eCl@ss 10.0.1 | 27400629 |
| eCl@ss 4.0    | 24190200 |
| eCl@ss 4.1    | 24190200 |
| eCl@ss 5.0    | 27149100 |
| eCl@ss 5.1    | 27141100 |
| eCl@ss 6.0    | 27149100 |
| eCl@ss 7.0    | 27149129 |
| eCl@ss 8.0    | 27149129 |
| eCl@ss 9.0    | 27400629 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC000761 |
| ETIM 4.0 | EC000761 |
| ETIM 5.0 | EC001288 |
| ETIM 6.0 | EC001288 |
| ETIM 7.0 | EC001288 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211811 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11     | 39121410 |
| UNSPSC 12.01  | 39121410 |
| UNSPSC 13.2   | 39131504 |
| UNSPSC 18.0   | 39131504 |
| UNSPSC 19.0   | 39131504 |
| UNSPSC 20.0   | 39131504 |
| UNSPSC 21.0   | 39131504 |