

Fuse plug - ST-SILED 24 - 0920452

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Fuse plug, Nominal current: 6.3 A, Length: 45.4 mm, Width: 9.9 mm, Color: black

The figure shows a similar product

Key Commercial Data

Packing unit	1 pc
GTIN	 4 017918 010256
Weight per Piece (excluding packing)	9.63 g
Custom tariff number	85369010
Country of origin	Poland

Technical data

General

Note	If the fuse is defective, the downstream circuit is not off load
Color	black
Insulating material	PA
Flammability rating according to UL 94	V2

Dimensions

Width	9.9 mm
Length	45.4 mm

General

Fuse	G / 5 x 20 / 5 x 25 / 5 x 30
Insulating material group	CTI 600
Nominal current I_N	6.3 A
Nominal voltage U_N	400 V

Connection data

Connection method	Plug connection
-------------------	-----------------

Fuse plug - ST-SILED 24 - 0920452

Technical data

Standards and Regulations

Connection in acc. with standard	CSA
Flammability rating according to UL 94	V2

Classifications

eCl@ss

eCl@ss 4.0	27141199
eCl@ss 4.1	27141199
eCl@ss 5.0	27141145
eCl@ss 5.1	27141145
eCl@ss 6.0	27141149
eCl@ss 7.0	27141149
eCl@ss 8.0	27142001

ETIM

ETIM 2.0	EC000897
ETIM 3.0	EC000897
ETIM 4.0	EC002018
ETIM 5.0	EC000036

UNSPSC

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121409
UNSPSC 11	39121409
UNSPSC 12.01	39121409
UNSPSC 13.2	39121409

Approvals

Approvals

Approvals

CSA / EAC

Ex Approvals

Fuse plug - ST-SILED 24 - 0920452

Approvals

Approvals submitted

Approval details

CSA 	
Nominal current IN	10 A
Nominal voltage UN	300 V

EAC
