

Cable marker - UCT-WMTBA (24X4) - 1014082

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

Cable marker, Sheet, white, unlabeled, can be labeled with: THERMOMARK PRIME, THERMOMARK CARD, BLUEMARK CLED, BLUEMARK LED, TOPMARK LASER, Mounting type: Assembly with cable binders, Cable diameter: >5 mm, Lettering field: 24 x 4 mm



Why buy this product

- The UCT-WMTBA ... UniCard labeling range includes markers that can be secured using standard cable binders
- Labeling service: Phoenix Contact can custom-label all UniCard markers according to your requirements
- The format automatically ensures printing with a high degree of positioning accuracy



Key Commercial Data

| Packing unit | 1 STK |
|--------------------------------------|-----------------|
| Minimum order quantity | 10 STK |
| GTIN | 4 046356 781343 |
| GTIN | 4046356781343 |
| Weight per Piece (excluding packing) | 10.000 g |
| Custom tariff number | 39269097 |
| Country of origin | Germany |

Technical data

Dimensions

| Length (b) | 24 mm |
|------------|-------|
| Width (a) | 4 mm |

Ambient conditions

| Ambient temperature (operation) | -40 °C 120 °C |
|---------------------------------|---------------|
|---------------------------------|---------------|

General



Cable marker - UCT-WMTBA (24X4) - 1014082

Technical data

General

| Color | white |
|---|--|
| Components | free from silicone, halogen, and cadmium |
| Flammability rating according to UL 94 | V0 |
| Material | PC |
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
| Number of individual labels | 15 |
| Number of individual labels per row | 5 |
| RoHS compliant | Yes |
| Printability | Thermal transfer |
| | UV LED technology |
| Device | 5146464 THERMOMARK CARD |
| | 5147999 BLUEMARK CLED |
| Test for substances that would hinder coating with paint or varnish | VW PV 3.10.7:2005-02 |
| Result | Test passed |
| Test specification weathering-resistance | Following ISO 4892-2:2013-03 |
| Test duration | 96 h |
| Wipe resistance test result | Test passed |
| Salt spray test specification | DIN EN 60068-2-11:2000-02 |
| Salt spray testing result | Test passed |
| Wipe resistance of test specification inscriptions | DIN EN 61010-1 (VDE 0411-1):2011-07 |
| Result | Test passed |
| Marking mounting type | Assembly with cable binders |

Standards and Regulations

| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
|--|-----------------------------|
| Flammability rating according to UL 94 | V0 |

Phoenix Contact 2017 © - all rights reserved http://www.phoenixcontact.com