

Crimping pliers - CRIMPFOX 6T - 1212037

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Crimping pliers, for ferrules without insulating collar according to DIN 46228 Part 1 and ferrules with insulating collar according to DIN 46228 Part 4, 0.25 mm² ... 6 mm², lateral entry, trapezoidal crimp

Product Features

- Comprehensive range of crimping pliers
- All ferrules can be optimally crimped with a minimum amount of effort even in the case of large conductor cross sections
- Marked die stations for precise processing of corresponding cross sections
- Consistently high crimping quality
- Unlockable pressure lock



Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	520.0 g
Custom tariff number	82032000
Country of origin	Sweden

Technical data

Dimensions

Length (b)	220 mm
Width (a)	22.5 mm
Height	72 mm

General

Color	black
Compression	Trapezoidal crimp
Type of contact	Insulated and uninsulated ferrules



Crimping pliers - CRIMPFOX 6T - 1212037

Technical data

General

Designation	Crimping position 1	
Min. cross section	0.25 mm²	
Max. cross section	6 mm²	
AWG min	24	
AWG max	10	
Designation	Crimping position 2	
	Crimping position 3	
Die station	Crimping position 4	
	Crimping position 5	

Classifications

eCl@ss

eCl@ss 4.0	21040301
eCl@ss 4.1	21040301
eCl@ss 5.0	21040301
eCl@ss 5.1	21040301
eCl@ss 6.0	21043811
eCl@ss 7.0	21043811
eCl@ss 8.0	21049090

ETIM

ETIM 2.0	EC001186
ETIM 3.0	EC001186
ETIM 4.0	EC001186
ETIM 5.0	EC000168

UNSPSC

UNSPSC 6.01	27112118
UNSPSC 7.0901	27111518
UNSPSC 11	23171604
UNSPSC 12.01	27111518
UNSPSC 13.2	27111518

Approvals


Approvals



Crimping pliers - CRIMPFOX 6T - 1212037

Approvals	
Approvals	
EAC	
Ex Approvals	
Approvals submitted	
Approval details	
EAC	

Drawings



Phoenix Contact 2016 © - all rights reserved http://www.phoenixcontact.com