

Crimping pliers - CRIMPFOX-DSUB 5 - 1212111

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Crimping pliers for D-SUB contacts, high-density, 0.08 - 0.5 mm², B-crimp, including contact locator

Product Features

- Lateral conductor entry
- Unlockable pressure lock



Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	440.0 g
Custom tariff number	82032000
Country of origin	Sweden

Technical data

Dimensions

Length (b)	198 mm
Width (a)	18 mm
Height	59 mm

General

Color	black
Compression	B crimp
Type of contact	D-SUB (standard and high-density)
Designation	Crimping position 1
Min. cross section	0.08 mm²
Max. cross section	0.22 mm²
AWG min	28

Crimping pliers - CRIMPFOX-DSUB 5 - 1212111

Technical data

General

AWG max	26
Designation	Crimping position 2
Min. cross section	0.08 mm ²
Max. cross section	0.22 mm ²
AWG min	28
AWG max	26
Designation	Crimping position 3
Min. cross section	0.22 mm ²
Max. cross section	0.5 mm ²
AWG min	26
AWG max	22

Classifications

eCl@ss

eCl@ss 4.0	21040301
eCl@ss 4.1	21040301
eCl@ss 5.0	21040301
eCl@ss 5.1	21040301
eCl@ss 6.0	21043811
eCl@ss 7.0	21043811
eCl@ss 8.0	21043811
eCl@ss 9.0	21043811

ETIM

ETIM 2.0	EC001186
ETIM 3.0	EC001186
ETIM 4.0	EC001186
ETIM 5.0	EC000168

UNSPSC

UNSPSC 6.01	27112118
UNSPSC 7.0901	27111518
UNSPSC 11	23171604
UNSPSC 12.01	27111518
UNSPSC 13.2	27111518

Crimping pliers - CRIMPFOX-DSUB 5 - 1212111

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approvals submitted

Approval details

EAC

Drawings

Product drawing

