

DIN rail perforated - NS 15 AL PERF 2000MM - 1401763

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



DIN rail, material: Aluminum, perforated, height 5.5 mm, width 15 mm, length: 2 m

Product Features

- All DIN rails are also available cut to length
- If you require greater quantities, the same article is available in a unit pack of 25 pcs. (50 m)
- Particular attention has been paid to high dimensional accuracy and surface tempering
- The design of the DIN rails corresponds to European standard EN 60715



Key Commercial Data

Packing unit	1 M
Minimum order quantity	5 M
GTIN	 4 017918 020521
Weight per Piece (excluding packing)	60.0 g
Custom tariff number	76042990
Country of origin	Germany

Technical data

Dimensions

Height	5 mm
Length	2000 mm
Width	15 mm

General

Material	Aluminum
Coating	uncoated

DIN rail perforated - NS 15 AL PERF 2000MM - 1401763

Technical data

General

Color	silver
Test standard	In acc. with EN 60715: 2001
Nominal current I_N	1920 A

Standards and Regulations

Test standard	In acc. with EN 60715: 2001
Connection in acc. with standard	IEC / EN

Classifications

eCl@ss

eCl@ss 4.0	27110804
eCl@ss 4.1	27110804
eCl@ss 5.0	27141143
eCl@ss 5.1	27141143
eCl@ss 6.0	27400602
eCl@ss 7.0	27400602
eCl@ss 8.0	27400602
eCl@ss 9.0	27400602

ETIM

ETIM 2.0	EC001285
ETIM 3.0	EC001285
ETIM 4.0	EC000212
ETIM 5.0	EC000212

UNSPSC

UNSPSC 6.01	30212109
UNSPSC 7.0901	39121708
UNSPSC 11	39121708
UNSPSC 12.01	39121708
UNSPSC 13.2	39121708

Drawings

DIN rail perforated - NS 15 AL PERF 2000MM - 1401763

Dimensional drawing

