

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



EVO connector set, B16 series, plastic housing, consisting of sleeve housing, panel mounting base, push-in contact inserts: 1407731, 1407732, 1407647, 1407642, 1407670

Product Features

- Lower costs than metal version
- Labeling option using 9 x 20 mm marking label
- Low weight
- Lower risk of condensation
- Both contact insert PE sheets are connected by means of a metal frame integrated in the sleeve housing
- Metal inlays ensure leading PE contact with angled plugs
- Completely corrosion-resistant
- Halogen-free plastic
- Impact test according to IK 08
- Marking label can be attached



Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	500.0 g
Custom tariff number	85366990
Country of origin	Germany

Technical data

General

Number of positions	16+PE
Туре	B16
Connection method	Push-in connection
Cable exit	straight



Technical data

General

Degree of protection for housing	IP66	
	IP54 (with closed protective cover)	
	4 (UL50e / NEMA 250)	
	4X (UL50e / NEMA 250)	
	12 (UL50e / NEMA 250)	
Connection method	Push-in connection	
Rated voltage (III/3)	500 V	
Rated surge voltage	6 kV	
Rated current	16 A	

Standards and Regulations

Flammability rating according to UL 94	V0

Articles in set

Contact insert - HC-B 16-I-PT-F - 1407731



HEAVYCON socket insert, B16 series, 16 + PE-pos., push-in connection

Contact insert - HC-B 16-I-PT-M - 1407732



HEAVYCON pin insert, B16 series, 16 + PE-pos., push-in connection

Housing - HC-EVO-B16-BWSC-PLRBK - 1407647



HEAVYCON EVO panel mounting base, plastic, B16, with single locking latch, height: 30.5 mm, with flat gasket, with protective cover



Articles in set

Housing - HC-EVO-B16-HHFS-PLBK - 1407642



HEAVYCON EVO sleeve housing, plastic, with bayonet flange for EVO screw connection, B16, for single locking latch, height: 76 mm, without EVO screw connection

Cable gland - HC-B-G-M25-PLRBK - 1407670



EVO plastic cable gland with bayonet locking, for housing series B, size M25, cable diameter: 9 ... 17 mm

Classifications

eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27143424
eCl@ss 5.1	27143424
eCl@ss 6.0	27143424
eCl@ss 7.0	27440209
eCl@ss 8.0	27440101

ETIM


ETIM 3.0	EC000438
ETIM 4.0	EC000437
ETIM 5.0	EC000437


UNSPSC

UNSPSC 6.01	30211923
UNSPSC 7.0901	39121522
UNSPSC 11	39121522
UNSPSC 12.01	39121522
UNSPSC 13.2	39121522



Approvals			
Approvals			
Approvals			
EAC / EAC			
Ex Approvals			
Approvals submitted			
Approval details			
EAC			
EAC			
Drawings			
Schematic dia	gram	Schematic diagram	





Pin assignment, connection side, pin

Pin assignment, connection side, socket



32

53

Connector set - HC-EVO-B16PT-BWSC-HH-M25-PLRBK - 1408793

Diagram

32
28
40
20
16
12
0 = 2,5 mm² HC-B 06 PT
40
2 = 2,5 mm² HC-B 10 PT
40
2 = 2,5 mm² HC-B 24 PT
0 10 20 30 40 50 60 70 80 90 100 110

Ambient temperature [°C]

Dimensional drawing

103


114

Derating diagram

Dimensional drawing

Ø4,5

Dimensional drawing



Panel cutout

Phoenix Contact 2016 © - all rights reserved http://www.phoenixcontact.com