

Flush-type connector - SACC-E-MINM-5CON-NPT12-U40/1,0 - 1420959

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



DeviceNet™ thick flush-type plug, 5-pos., 7/8", front mounting with 7/8" fastening thread, with 1.0 m PE litz wire

RoHS

Key Commercial Data

Packing unit	1 STK
Custom tariff number	85444290
Country of origin	Mexico

Technical data

Dimensions

Length of cable	1 m
-----------------	-----

Ambient conditions

Ambient temperature (operation)	-20 °C ... 80 °C (Plug)
Degree of protection	IP68

General

Rated current at 40°C	8 A
Rated voltage	300 V AC/DC
Number of positions	5
Insulation resistance	≥ 100 MΩ
Standards/regulations	UL 2238
Status display	No
Overvoltage category	UL 2238 Section 38
Connection method	Individual wires
Torque	10 lb _F -in.
	1.12 Nm

Flush-type connector - SACC-E-MINM-5CON-NPT12-U40/1,0 - 1420959

Technical data

General

Mounting type	Front mounting, with 1/2 inch-14 NPT mounting thread 7/8"
---------------	---

Material

Flammability rating according to UL 94	V-0
Contact material	Copper alloy
Contact surface material	Au
Contact carrier material	PVC
Material, knurls	Anodized aluminum

Cable

Cable type	CAN Bus/DeviceNet
Cable abbreviation	U40
Cable structure	2xAWG18+2xAWG15+1xAWG18
Conductor cross section	2 x AWG 18 data cable
	2 x AWG 15 power supply
	1 x AWG 18 drain wire
AWG signal line	18
AWG power supply	15
Conductor structure signal line	19 x AWG 30
Conductor structure, voltage supply	19 x AWG 28
Core diameter including insulation	11.43 mm
Wire colors	Red-black, blue-white
Twisted pairs	2 cores to the pair
Type of pair shielding	Plastic-coated aluminum foil, aluminum side outside
Overall twist	2 pairs and one drain wire to the core
Optical shield covering	65 %
External sheath, color	gray
Outer sheath, material	PVC
Material conductor insulation	Foamed PE (Data)
	PVC (Power supply)
Standards/specifications	UL 2238


Standards and Regulations

Standards/regulations	UL 2238
Flammability rating according to UL 94	V-0

Drawings

Flush-type connector - SACC-E-MINM-5CON-NPT12-U40/1,0 - 1420959

Dimensional drawing




7/8" flush-type plug

Circuit diagram



Contact assignment of the 7/8" plug

Schematic diagram



Pin assignment, plug, 7/8"-16UNF, 5-pos., view of male side