

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Y-distributor/ connector M12, with female connector M8, 3-pos. distributor



Key Commercial Data

Packing unit	1 pc
Minimum order quantity	5 pc
GTIN	4 017918 166939
Weight per Piece (excluding packing)	13.51 g
Custom tariff number	85366990
Country of origin	Poland

Technical data

Dimensions

Center distance	12 mm
-----------------	-------

Ambient conditions

Ambient temperature (operation)	-25 °C 90 °C
Degree of protection	IP65
	IP67

General

Rated current at 40°C	4 A
Rated voltage	60 V
Number of positions	4
Insulation resistance	$\geq 100 \ \text{M}\Omega$
Coding	A - standard



Technical data

General

Standards/regulations	M12 connector IEC 61076-2-101		
	M8 connector IEC 61076-2-104		
Status display	No		
Overvoltage category	II		
Degree of pollution	3		
Insertion/withdrawal cycles	≥ 100		
Torque	0.4 Nm (M12 connector)		
	0.2 Nm (M8 connectors)		

Material

Flammability rating according to UL 94	НВ
Contact material	CuZn
Contact surface material	Ni/Au
Contact carrier material	TPU GF
Material of grip body	TPU, hardly inflammable, self-extinguishing
Material, knurls	Zinc die-cast, nickel-plated
Sealing material	NBR

Cable

Standards and Regulations

Standard designation	M12 connector
Standards/regulations	IEC 61076-2-101
Standard designation	M8 connector
Standards/regulations	IEC 61076-2-104
Flammability rating according to UL 94	НВ

Classifications

eCl@ss

eCl@ss 4.0	27060306
eCl@ss 4.1	27060306
eCl@ss 5.0	27061801
eCl@ss 5.1	27061801
eCl@ss 6.0	27061801
eCl@ss 7.0	27061801
eCl@ss 8.0	27440104
eCl@ss 9.0	27440106



Classifications

ETIM

ETIM 2.0	EC000830
ETIM 3.0	EC001855
ETIM 4.0	EC001855
ETIM 5.0	EC002062

UNSPSC

UNSPSC 6.01	31251501
UNSPSC 7.0901	31251501
UNSPSC 11	31251501
UNSPSC 12.01	31251501
UNSPSC 13.2	31251501

Approvals		
Approvals		
Approvals		
EAC / EAC		
Ex Approvals		
Approvals submitted		
Approval details		
EAC		

Drawings

EAC



Schematic diagram




Schematic diagram




Pin assignment M12 plug, 4-pos., A-coded, view plug side

Pin assignment M8 socket, 3-pos., view female side

Dimensional drawing




Circuit diagram



M12 Y distributor

Contact assignment of the M12/M8 Y distributor

Schematic diagram



Layout of connector pin assignments

Phoenix Contact 2016 © - all rights reserved http://www.phoenixcontact.com