

D-SUB pressure nut - VS-PG11 (3- 7) - 1688117

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



D-SUB cap nut with line seal, for conductor diameter of 3 mm ... 7 mm, for sleeve housing VS-15-...



Key Commercial Data

Packing unit	1 pc
Minimum order quantity	5 pc
Weight per Piece (excluding packing)	4.4 g
Custom tariff number	39269097
Country of origin	Germany

Technical data

Mechanical characteristics

External cable diameter	3 mm ... 7 mm
Type of cable	Round cable
Color	gray

Ambient conditions

Ambient temperature (operation)	-40 °C ... 80 °C
Ambient temperature (assembly)	-20 °C ... 80 °C

Material data

Flammability rating according to UL 94	V0
Housing material	PA
Sealing material	Neoprene
Seal material	Neoprene

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

D-SUB pressure nut - VS-PG11 (3- 7) - 1688117

Classifications

eCl@ss

eCl@ss 4.0	27140816
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27261203
eCl@ss 7.0	27440290
eCl@ss 8.0	27069215

ETIM

ETIM 2.0	EC000437
ETIM 3.0	EC000437
ETIM 4.0	EC000437
ETIM 5.0	EC000814

UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501

Drawings

Dimensional
drawing

D-
SUB
cap
nut