

D-SUB power contact - VS-ST-LK-3,6/22,4/2,6 - 1688243

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Power contacts, for D-SUB combination inserts, pin, solder cup, straight, rated current 20 A, gold-plated



Key Commercial Data

Packing unit	1 pc
Minimum order quantity	30 pc
Weight per Piece (excluding packing)	2.16 g
Custom tariff number	85366990
Country of origin	Germany

Technical data

Mechanical characteristics

Insertion/withdrawal cycles	≥ 500
Connection method	Solder cup
Type of contact	Male connector
Conductor cross section	2 mm² ... 3.5 mm²
Connection cross section AWG	14 ... 12
Insertion force per signal contact	≤ 7.00 N
Extraction force per signal contact	approx. 5 N

Ambient conditions

Ambient temperature (operation)	-55 °C ... 155 °C
---------------------------------	-------------------

Material data

Contact material	Copper alloy
Contact surface material	Hard gold-plated over nickel

Electrical characteristics

D-SUB power contact - VS-ST-LK-3,6/22,4/2,6 - 1688243

Technical data

Electrical characteristics

Rated current	20 A
---------------	------

Classifications

eCl@ss

eCl@ss 4.0	27140816
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27260705
eCl@ss 7.0	27440204
eCl@ss 8.0	27440204

ETIM

ETIM 2.0	EC000438
ETIM 3.0	EC000438
ETIM 4.0	EC000796
ETIM 5.0	EC000796

UNSPSC

UNSPSC 6.01	30211923
UNSPSC 7.0901	39121522
UNSPSC 11	39121522
UNSPSC 12.01	39121522
UNSPSC 13.2	39121522

Approvals

Approvals

Approvals

EAC / EAC / EAC

Ex Approvals

Approvals submitted

D-SUB power contact - VS-ST-LK-3,6/22,4/2,6 - 1688243

Approvals

Approval details


EAC

EAC

EAC

Drawings

Dimensional drawing



D-SUB power contact pin