

D-SUB connector set - VS-15-SET-EMV - 1689132

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



D-SUB connector set, shell size 2, IP67 protection, with shrouds

The illustration shows the version
VS-09-SET-EMV

RoHS

Key Commercial Data

Packing unit	1 STK
Weight per Piece (excluding packing)	83.850 g
Custom tariff number	85366990
Country of origin	Germany

Technical data

Mechanical characteristics

Number of positions	15
Shielded	yes
Insertion/withdrawal cycles	≥ 1000
External cable diameter	3 mm ... 9 mm
Cable exit	Angled
Color	gray
Degree of protection	IP67
Design	D-SUB 15
Size of housing	2
No. of cable outlets	2

Ambient conditions

Ambient temperature (operation)	-40 °C ... 80 °C
---------------------------------	------------------

D-SUB connector set - VS-15-SET-EMV - 1689132

Technical data

Material data

Flammability rating according to UL 94	V0
Housing material	PA
Sealing material	Flat gasket: NBR; profile gasket: EPDM
Seal material	Flat gasket: NBR; profile gasket: EPDM
Cable seal material	CR/NBR

Electrical characteristics

Number of positions	15
Degree of pollution	2

Standards and Regulations


Flammability rating according to UL 94	V0
--	----

Environmental Product Compliance


China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Drawings

Dimensional drawing



Dimensional drawing




D-SUB sleeve housings

Panel cutout

D-SUB connector set - VS-15-SET-EMV - 1689132

Dimensional drawing



D-SUB panel mounting frame

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC B.01742