

DIN rail bus connectors - ME 17,5 TBUS ADAPTER KMGY - 2201757

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

DIN rail bus adapter for ME and ME-MAX, design width: 17.5 mm, 5 parallel positions, color: light gray (similar to RAL 7035)



Your advantages

- ✓ Space-saving DIN rail mounting



Key Commercial Data

Packing unit	1 pc
Minimum order quantity	50 pc
GTIN	 4 046356 909037
GTIN	4046356909037
Weight per Piece (excluding packing)	3.600 g
Custom tariff number	85366990
Country of origin	Germany

Technical data

Dimensions

Width	17.5 mm
Pitch	3.81 mm
Width [w]	17.5 mm

General

Insulating material	PA
Flammability rating according to UL 94	V0
Color	light gray

DIN rail bus connectors - ME 17,5 TBUS ADAPTER KMGY - 2201757

Technical data

General

Number of positions	5
---------------------	---

General product information

Type of note	Recommendation
Note	Material of contact pads for bus connector, galvanic gold (hard gold)

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Classifications

eCl@ss

eCl@ss 10.0.1	27440309
eCl@ss 5.0	27180500
eCl@ss 5.1	27180500
eCl@ss 6.0	27180800
eCl@ss 7.0	27182702
eCl@ss 8.0	27440309
eCl@ss 9.0	27440309

ETIM

ETIM 4.0	EC001031
ETIM 5.0	EC002638
ETIM 6.0	EC002638
ETIM 7.0	EC002638

UNSPSC

UNSPSC 13.2	31261501
UNSPSC 18.0	39121409
UNSPSC 19.0	39121409
UNSPSC 20.0	39121409
UNSPSC 21.0	39121409

Approvals

Approvals

DIN rail bus connectors - ME 17,5 TBUS ADAPTER KMGY - 2201757

Approvals

Approvals

UL Recognized / cUL Recognized / EAC / cULus Recognized

Ex Approvals

Approval details

UL Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	E118976-20151204
Nominal voltage UN		150 V	
Nominal current IN		8 A	

cUL Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	E118976-20151204
Nominal voltage UN		150 V	
Nominal current IN		6 A	

EAC		B.01742
-----	---	---------

cULus Recognized	
------------------	---