

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Installation component housing, Transparent hinged cover, Including insertion plate, width: 161.6 mm, color: transparent/light gray (7035)

### Your advantages

- ☑ Conforms to DIN EN 43880
- ▼ Tool-free mounting
- Available in overall widths from one to nine width units (17.8 mm ... 161.6 mm)
- Inflammability class V0 according to UL 94
- Variety of connection technologies
- ☑ Can be mounted on the DIN rail or the wall



### **Key Commercial Data**

Packing unit	1 pc
Minimum order quantity	10 pc
GTIN	4 0 4 6 3 5 6 2 9 9 4 5 9
GTIN	4046356299459
Weight per Piece (excluding packing)	33.900 g
Custom tariff number	85389099
Country of origin	Germany

### Technical data

#### Item properties

Brief article description	Housing cover



### Technical data

### Item properties

Туре	BC 161,6 DKL S TRANS
Order No.	2278542
Housing type	Installation component housing
Housing series	BC
Туре	Transparent hinged cover
Mounting type	hinged and can be sealed

### Dimensions

Width [ w ]	161.6 mm
Height [ h ]	45 mm

### Material data

Color (RAL)	transparent/light gray (7035)
Flammability rating according to UL 94	V0
Housing material	Polyamide

### Ambient conditions

Ambient temperature (storage/transport)	-40 °C 70 °C
Ambient temperature (assembly)	-5 °C 100 °C
Ambient temperature (operation)	-40 °C (depending on power dissipation)

### Packaging information

Pieces per package	10
Denomination packing units	Pcs.

### Standards and regulations

Flammability rating according to UL 94	V0
--	----

### **Environmental Product Compliance**

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

### Classifications

### eCl@ss

eCl@ss 4.0	27180400
eCl@ss 4.1	27180400
eCl@ss 5.0	27180500
eCl@ss 5.1	27180500
eCl@ss 6.0	27180800
eCl@ss 7.0	27182702



### Classifications

### eCl@ss

eCl@ss 8.0	27182702
eCl@ss 9.0	27182702

### **ETIM**

ETIM 2.0	EC001031
ETIM 3.0	EC001031
ETIM 4.0	EC001031
ETIM 5.0	EC001031
ETIM 6.0	EC001031
ETIM 7.0	EC001031

### **UNSPSC**

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501

### Approvals

Approvals

Approvals

UL Recognized / EAC

Ex Approvals

### Approval details

UL Recognized http://database.ul.com/cgi-bin/XYV/ter

http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm FILE E 240868

EAC B.01742



### Accessories

Accessories

Fiber optic

Fiber optic - HS LC-V-D3/ R2XC1-5,08 - 2202311



Light guides, passive, rigid, can be used for the BC housing range (housing must be processed)

Fiber optic - HS LC-V-D3/ R3XC1-5,08 - 2202312



Light guides, passive, rigid, can be used for the BC housing range (housing must be processed)

Phoenix Contact 2019 @ - all rights reserved http://www.phoenixcontact.com