

Safety relays - PSR-MC20-3NO-1DO-24DC-SP-DUMMY - 2702347

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Safety relay for emergency stop/safety doors up to SILCL 1, Cat. 1, PL c, depending on the application up to SILCL 3, Cat. 4, PL e, 1-channel operation, automatic/manual start, 3 enabling current paths, $U_s = 24 \text{ V DC}$, plug-in spring-cage terminal block

The illustration shows the standard type

RoHS

Key Commercial Data

Packing unit	1 STK
GTIN	 4 055626 129716
GTIN	4055626129716
Weight per Piece (excluding packing)	120.000 g
Custom tariff number	90230080
Country of origin	Germany

Technical data

Input data

Rated control circuit supply voltage U_s	24 V DC
--	---------

Output data

Contact type	3 enabling current paths
--------------	--------------------------

General

Net weight	112.6 g
------------	---------

Connection data

Connection method	Spring-cage connection
pluggable	Yes

Safety relays - PSR-MC20-3NO-1DO-24DC-SP-DUMMY - 2702347

Technical data

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Classifications

eCl@ss

eCl@ss 5.1	27371901
eCl@ss 6.0	27371819
eCl@ss 8.0	27371819
eCl@ss 9.0	27371819

ETIM

ETIM 5.0	EC001449
ETIM 6.0	EC001449

UNSPSC

UNSPSC 13.2	39121501
-------------	----------