

LED machine light - PLD M 160 W-95/105 896 - 2702478

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



LED machine light, 24 V DC, Degree of protection IP67, Emission angle 95 °/105 °, Color temperature 5800 K, Length 896 mm, Light housing: Anodized aluminum, Light cover: Satined acrylic, pivoting, including mounting accessories

Product Description

This LED machine light is designed to provide illumination inside or on machinery. Due to the narrow design, it can be mounted even where space is at a premium. In the light holder supplied, the light can swivel and the lighting can therefore be optimally aligned. The satin-finished plastic cover prevents glare for the machine operator.

Why buy this product

- ✓ Narrow design enables mounting even in confined spaces
- ✓ Ready to connect by means of punched-on 3 m supply line
- ✓ Focused illumination, thanks to swivel action
- ✓ IP67 protection enables use even in wet environments
- ✓ ETL approval permits use on the North American market
- ✓ Particularly economical thanks to energy-efficient LED technology and an LED service life of at least 50,000 h

RoHS

Key Commercial Data

Packing unit	1 STK
GTIN	 4 055626 213842
GTIN	4055626213842
Custom tariff number	94054099
Country of origin	Germany

Technical data

Dimensions

Width	22.5 mm
-------	---------

LED machine light - PLD M 160 W-95/105 896 - 2702478

Technical data

Dimensions

Height	23 mm
Length	896 mm

Ambient conditions

Ambient temperature (operation)	0 °C ... 40 °C
Ambient temperature (storage/transport)	-10 °C ... 50 °C
Permissible humidity (operation)	95 %
Permissible humidity (storage/transport)	95 % (non-condensing)
Air pressure (operation)	69 kPa ... 102 kPa
Air pressure (storage/transport)	69 kPa ... 102 kPa
Degree of protection	IP67

General

Net weight	800 g
Mounting type	Screw mounting

Power supply for module electronics

Connection method	open cable end
Cable length	approx. 3 m
Supply voltage	24 V DC
Supply voltage range	22 V DC ... 25 V DC
Current consumption	typ. 0.875 A (at 24 V DC)
Power consumption	approx. 21 W (at 24 V DC)
Type of protection	Surge protection

Light properties

Source of light type	LED
Number of LEDs	36
Service life, lighting appliance	50,000 h (L70)
Light color	daylight white
Color temperature	5800 K $\pm$ 10 %
Color rendering index	75
Luminous flux	approx. 900 lm (Net luminous flux)
Illumination	max. 833 lx (50 cm distance)
Average illumination	449 lx (Distance of 50 cm over 1 m ² area)
Emission angle	95 ° (C0-C180)

Standards and Regulations

Protection class	III, IEC 61140, EN 61140, VDE 0140-1
------------------	--------------------------------------

Environmental Product Compliance

LED machine light - PLD M 160 W-95/105 896 - 2702478


Technical data

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values


Drawings

Diagram




Illuminance distribution
(distance d = 0.5 m)

Diagram



Luminous intensity distribution (LID)
(red line: C0 - C180, blue line: C90 - C270)

Dimensional drawing



Approvals

Approvals

Approvals

ETLus / cETL / cETLus

Ex Approvals

LED machine light - PLD M 160 W-95/105 896 - 2702478

Approvals

Approval details

ETLus		http://www.intertek.com	LV-Lighting-Systems
cETL		http://www.intertek.com	Luminaires
cETLus		http://www.intertek.com	