

Inline terminal - IB IL AI 4/U/0-10-ECO - 2702496

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Inline ECO, Analog input terminal, Analog inputs: 4, 0 V ... 10 V, Connection technology: 2-wire, Transmission speed in the local bus 500 kbps, Degree of protection IP20, including Inline connector

Product Description

The terminal is designed for use within an Inline station.

The measured values are depicted in standardized representation format.

Inline ECO terminals are approved for the temperature range from 0°C to +55°C. The electronics base and Inline connector are supplied as standard.

Why buy this product

- ☒ 4 analog input channels
- ☒ Connection of sensors in 2-wire technology
- ☒ Voltage range: 0 V ... 10 V
- ☒ Data format: standardized representation
- ☒ Resolution: 12 bits
- ☒ Diagnostic indicator

RoHS

Key Commercial Data

Packing unit	1 STK
GTIN	 4 055626 205021
GTIN	4055626205021
Custom tariff number	85389091
Country of origin	Germany

Technical data

Note

Inline terminal - IB IL AI 4/U/0-10-ECO - 2702496

Technical data

Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

Dimensions

Width	12.2 mm
Height	119.8 mm
Depth	71.5 mm

Ambient conditions

Ambient temperature (operation)	0 °C ... 55 °C
Ambient temperature (storage/transport)	-25 °C ... 85 °C
Permissible humidity (operation)	10 % ... 95 % (according to DIN EN 61131-2)
Permissible humidity (storage/transport)	10 % ... 95 % (according to DIN EN 61131-2)
Air pressure (operation)	70 kPa ... 106 kPa (up to 3000 m above sea level)
Air pressure (storage/transport)	70 kPa ... 106 kPa (up to 3000 m above sea level)
Degree of protection	IP20

General

Mounting type	DIN rail
Net weight	69 g
Note on weight specifications	with connector
Diagnostics messages	Failure of the internal I/O supply I/O error message sent to the bus coupler
	Checksum error I/O error message sent to the bus coupler

Interfaces

Fieldbus system	Lokalbus
Designation	Inline local bus
Connection method	Inline data jumper
Transmission speed	500 kbps

Inline potentials

Communications power U_L	7.5 V DC
Current consumption from U_L	typ. 60 mA
I/O supply voltage U_{ANA}	24 V DC
Current consumption from U_{ANA}	typ. 15 mA
Power consumption	typ. 0.8 W
	max. 0.9 W

Analog inputs

Description of the input	Single-ended inputs, voltage
Input name	Analog inputs

Inline terminal - IB IL AI 4/U/0-10-ECO - 2702496

Technical data

Analog inputs

Number of inputs	4
Connection method	Inline connector
Connection technology	2-wire
Note regarding the connection technology	Shielded, twisted pair
Resolution A/D	12 bit
Type of protection	Overload protection
Protective circuit/component	±30 V DC, maximum
Data formats	Standardized representation
Measured value representation	16 bits
Voltage input signal	0 V ... 10 V
Input resistance of voltage input	115 kΩ

Electrical isolation

Test section	Bus logic (local bus, communications power) 500 V AC 50 Hz 1 min.
	Analog I/O 500 V AC 50 Hz 1 min.
	Functional earth ground 500 V AC 50 Hz 1 min.

Standards and Regulations

Protection class	III, IEC 61140, EN 61140, VDE 0140-1
------------------	--------------------------------------

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values